



SECTION A-A

THIS DRAWING IS THE CONFIDENTIAL AND PROPRIETARY INFORMATION OF VINCICKER ENCLOSURE SYSTEMS, INC. AND SHALL NOT BE REPRODUCED OR INCORPORATED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF VINCICKER ENCLOSURE SYSTEMS, INC.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES DECIMALS .001		VINCICKER ENCLOSURE SYSTEMS, INC.	
DRAWN BY: KEITH CHAPMAN		VINCICKER PART# V11210HWLL2	
DATE: 12/13/01		DWG NO. V11210HWLL2	
CHECKED BY: DESIGN	SCALE: FULL	SHEET: 1	REV: 0

- NOTES:
- ENCLOSURE MATERIAL MADE OF GRAY (RAL 7036) HOT MOLDED FIBERGLASS REINFORCED POLYESTER.
 - UL LISTED PER STD. 508 (TITLE# E54315)
 - CSA CERTIFIED PER STD. C22.2 NUL 94 (TITLE# LR6508)
 - NEMA RATED TYPE 3, 3R, 3S, 4, 4X, 12 AND 13.
 - IEC 529 RATED IP 68.
 - TEMPERATURE RANGES FROM -50 DEG C TO 150 DEG C.
 - SELF EXTINGUISHING AND HALOGEN FREE.
 - ACCESSORIES INCLUDE: BACK PANELS, DEAD FRONT PANELS, HINGED FRONT PLATES, HINGED COVERS, PRINT POCKETS, LATCHES, WINDOWS, AND VENTILATORS.
 - CABINETS ARE MAINTENANCE FREE AND CORROSION RESISTANT.