



IMPORTANT PRODUCT INFORMATION AND WARNINGS:

- **Always disconnect the power before installing and before cleaning or other maintenance.**
- **This fixture is dimmable only with AC Phase Trailing-edge dimmers.**
- **Consult a qualified, licensed electrician to ensure correct branch circuit conductor.**
- **Dusting: Use a clean, dry cloth.**
- **Cleaning: To protect the finish, avoid using any harsh abrasives or chemicals.**
- Please read all included assembly instructions and warnings carefully before installing this product. Contact LUX LED Lights Customer Service if you have any questions or concerns.
- Before installation, please confirm that the fixture is compatible with the supply voltage and dimming system, if present.
- Do not open any factory sealed components and avoid touching the LEDs with your hands or any object.
- Although LUX LED Lights fixtures are equipped with protective drive electronics, LED fixtures are sensitive to variations in supply power and to power surges. Do not install LED fixtures on the same circuit as any motors, appliances, or HVAC systems.
- Do not remove or bypass the LED driver that is provided with the fixture. Do not replace the driver or substitute with another power supply.
- Do not disconnect any factory wiring in the fixture.
- The mounting hardware provided is for a typical installation and should be used at the discretion of a licensed electrician. Always use hardware that is appropriate for the actual installation.
- Wire LUX Brooklyn Sconces in parallel and on independent leads. Do not wire multiple fixtures in series.

ASSEMBLY INSTRUCTIONS

1. Shut off power to the junction box.
2. Attach the mounting plate to the junction box with the appropriate screws.
3. Make appropriate electrical connections using wire nuts:
 - Connect the driver's neutral wire (white) to the neutral junction box wire.
 - Connect the driver's line wire (black) to the junction box line wire.
 - Connect fixture's ground wire (green or green/yellow) to an appropriate earth ground in the junction box. If no ground is present in junction box, connect fixture's ground wire to the mounting plate using the green screw (included).
4. Carefully place the wires in the junction box.
5. Install the fixture to the mounting plate using the 4mm set screws provided. Tighten the set screws using the Allen wrench provided.
6. Restore power to the fixture.

CUSTOMER SERVICE:

For questions and assistance please contact us at:
800.922.3233 • customerservice@mightybright.com
www.lux-led-lights.com

