

Flamingo

Design by Antoni Arola.

Reference

1550.

Application

Pendants

Installation type

Surface mounted

Description

The designer Antoni Arola has created the Flamingo lamps collection for Vibia. A collection of pendant lights that provides an ambient light through a thermoplastic translucent diffuser which performs like a spot light thanks to its LED light source.

Diffuser

Acrylic diffuser

Materials

LED support: Aluminum

Shade: Acrylic

Rods: Steel

Canopy: Steel

Finishes



1550-18 Graphite (Flamingo RAL 7016)




1550-20 Gold (Flamingo gold)



1550-93 White (Flamingo RAL 9016)

Sketch




Electrical characteristics

3 x LED 5.6W 500mA

Total 16.8 W



VIBIA



Light source: 2700K CRI >90 2083 lm 124 lm/W

Fixture: 1652 lm 98 lm/W

Driver included: CC - Constant Current 500 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or Lutron ECO

Technical characteristics

- Cable can be adjusted in the field. 157" max.


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 56.06 lm/W

Isolux : Floor

Coordinate system : CG

Light position :

Total flux : 1664.91 lm

X=0.00m Y=0.00m Z=2.50m

Maximum value : 1503.18 cd

Light position : C=0.00 G=10.00

Symmetry on the planes : Asymmetric

Certificates

