

Flock of Light

Studio Toer



Flock of Light, by Studio Toer, transforms from a light and airy artistic design piece at daytime, to a swarm of bright lights at night. Flock of Light comes in two sizes: 11 and 21, after the number of light sources. Both sizes are made from brass cups, bronze wires and semi-transparent polycarbonate diffusers. This suspension lamp brings a bright, warm and poetic glow right after dark. A Flock of Light captured in stillness.

Detailing



Like standing amidst a swarm of buzzing bright lights. Flock of Light captures the magic of a warm summer evening.

Flock of Light / 11

Dimensions

80cm | 31.5"

65cm | 25.6"



65cm | 25.6"



Product

Width 80cm | 31.5"
Height 65cm | 25.6"
Depth 65cm | 25.6"
Weight netto 0.9kg | 1.98lbs

Packaging

Width 55cm | 21.7"
Height 55cm | 21.7"
Cubage 0.19m³ | 6.73ft³
Length 63cm | 24.8"
Weight 7 | 15.43lbs

Technical CE

Material

bronze wires, brass cups with semi-transparent polycarbonate diffusers

Energy label

Energy Label A+

Installation required

Yes

Lightsource type

LED

Lightsource included

Yes

Number of lightsources

11

Shape

Abstract

Input voltage

220-240

Frequency

50/60

Max power consumption

13W

Dimmable

Yes

Lampholder

LED (Solid state)

Lifetime
50000 hours
Cable colour
Transparent with tinned cores
Cable Length
250cm | 98.4"
Canopy
Pebble II White, ABS
Colour temperatue
2700 K
CRI
91
Light direction
All directions
Light output
1240 lm

Technical cULus

Material
bronze wires, brass cups with semi-transparent polycarbonate diffusers
Energy label
Energy Label A+
Installation required
Yes
Lightsource type
LED
Lightsource included
Yes
Number of lightsources
11
Shape
Abstract
Input voltage
110-130
Frequency
50/60
Max power consumption
13W
Dimmable
Yes
Lampholder
LED (Solid state)
Lifetime
50000 hours
Cable colour
Transparent with tinned cores
Cable Length
250cm | 98.4"
Canopy

Pebble II White, ABS

Colour temperature

2700 K

CRI

91

Light direction

All directions

Light output

1240 lm

Flock of Light / 21

Dimensions

135cm | 53.2"

85cm | 33.5"



80cm | 31.5"



Product

Width 135cm | 53.1"

Height 65cm | 25.6"

Depth 85cm | 33.5"

Weight netto 1.4kg | 3.09lbs

Packaging

Width 55cm | 21.7"

Height 75cm | 29.5"

Cubage 0.45m³ | 16.02ft³

Length 110cm | 43.3"

Weight 9 | 19.84lbs

Technical CE

Material

bronze wires, brass cups with semi-transparent polycarbonate diffusers

Energy label

Energy Label A+

Installation required

Yes

Lightsource type

LED

Lightsource included

Yes

Number of lightsources

21

Shape
Abstract
Input voltage
220-240
Frequency
50/60
Max power consumption
23W
Dimmable
Yes
Lampholder
LED (Solid state)
Lifetime
50000 hours
Cable colour
Transparent with tinned cores
Cable Length
250cm | 98.4"
Canopy
Pebble II White, ABS
Colour temperatue
2700 K
CRI
91
Light direction
All directions
Light output
2308 lm

Technical cULus

Material
bronze wires, brass cups with semi-transparent polycarbonate diffusers
Energy label
Energy Label A+
Installation required
Yes
Lightsource type
LED
Lightsource included
Yes
Number of lightsources
21
Shape
Abstract
Input voltage
110-130
Frequency
50/60
Max power consumption

23W
Dimmable
Yes
Lampholder
LED (Solid state)
Lifetime
50000 hours
Cable colour
Transparent with tinned cores
Cable Length
250cm | 98.4"
Canopy
Pebble II White, ABS
Colour temperatue
2700 K
CRI
91
Light direction
All directions
Light output
2308 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.
Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

Dimmer type

Mains dimmable (trailing edge / reverse phase)

Load type

Capacitive load (C-Type)
