

# PALMA

Design by Antoni Arola.

## Reference

**3700.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents an individual wall lamp. Its timeless sphere of light evolves towards the organic. Slightly flattened like the shape of the Earth, it gives off a warm and adjustable light.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

## Finish




**3700-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3700-93** Matt white lacquer (RAL 9016)

## Sketch



## Electrical characteristics



**Led** 2700K CRI >90 868 lm 93 lm/W

**Fixture:** 576.81 lm 49.6 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional DALI**

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0400 m<sup>3</sup> /

Gross weight 1.1 kg. / Net weight 2.1 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 576.81 lm

Maximum value : 107.81 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Symmetrical planes

270-90

Isolux : Isolux (Floor)

Light position :

X=0.00ft Y=0.00ft Z=8.20ft

## Certificates



# PALMA

Design by Antoni Arola.

## Reference

**3702.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents a horizontal wall lamp. It is expressed in a different way to the classical globe, new horizontal relationships at a large scale combined with vegetation.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)

## Finish




**3702-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3702-93** Matt white lacquer (RAL 9016)

## Sketch



## Electrical characteristics



**Led** 2700K CRI >90 868 lm 93 lm/W

**Fixture:** 576.51 lm 49.57 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional DALI**

## Technical characteristics

- Plants not included

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0597 m<sup>3</sup> /

Gross weight 3.9 kg. / Net weight 2.8 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Isolux : Isolux (Floor)

Coordinate system : CG

Light position :

Total flux : 576.51 lm

X=0.00ft Y=0.00ft Z=8.20ft

Maximum value : 68.00 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Symmetrical planes

270-90

## Certificates



# PALMA

Design by Antoni Arola.

## Reference

**3704.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents a horizontal wall lamp. It is expressed in a different way to the classical globe, new horizontal relationships at a large scale combined with vegetation.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)

## Finish




**3704-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3704-93** Matt white lacquer (RAL 9016)

## Sketch



## Electrical characteristics



**Led** 2700K CRI >90 1736 lm 93 lm/W

**Fixture:** 1141.52 lm 49.08 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional DALI**

## Technical characteristics

- Plants not included

## Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.1816 m<sup>3</sup> /

Gross weight 8.1 kg. / Net weight 5.4 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1141.52 lm

Maximum value : 66.39 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Asymmetric

Isolux : Isolux (Floor)

Light position :

X=0.00ft Y=0.00ft Z=8.20ft

## Certificates



# PALMA

Design by Antoni Arola.

## Reference

**3706.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents a horizontal wall lamp. It is expressed in a different way to the classical globe, new horizontal relationships at a large scale combined with vegetation.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)

## Finish




**3706-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3706-93** Matt white lacquer (RAL 9016)

## Sketch



## Electrical characteristics



**Led** 2700K CRI >90 2604 lm 93 lm/W

**Fixture:** 1712.28 lm 49.08 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional DALI**

## Technical characteristics

- Plants not included

## Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.2495 m<sup>3</sup> /

Gross weight 10.8 kg. / Net weight 7.5 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1712.28 lm

Maximum value : 66.39 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Asymmetric

Isolux : Isolux (Floor)

Light position :

X=0.00ft Y=0.00ft Z=8.20ft

## Certificates



# PALMA

Design by Antoni Arola.

## Reference

**3710.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents an individual wall lamp. Its timeless sphere of light evolves towards the organic. Slightly flattened like the shape of the Earth, it gives off a warm and adjustable light.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

## Finish




**3710-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3710-93** Matt white lacquer (RAL 9016)

## Sketch



## Electrical characteristics



**Led** 2700K CRI >90 868 lm 93 lm/W

**Fixture:** 576.51 lm 49.57 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional DALI**

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0400 m<sup>3</sup> /

Gross weight 2.1 kg. / Net weight 1.1 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 576.51 lm

Maximum value : 68.00 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Symmetrical planes  
270-90

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

## Certificates



# PALMA

Design by Antoni Arola.

# VIBIA

## Reference

**3714.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents a vertical wall lamp. It is expressed in a different way to the classical globe, new vertical relationships at a large scale combined with vegetation.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)

## Finish




**3714-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3714-93** Matt white lacquer (RAL 9016)

## Sketch



**Led** 2700K CRI >90 868 lm 93 lm/W

**Fixture:** 576.51 lm 49.57 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional DALI

## Technical characteristics

- Plants not included

## Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0654 m<sup>3</sup> /

Gross weight 5.8 kg. / Net weight 4.4 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Isolux : Isolux (Floor)

Coordinate system : CG

Light position :

Total flux : 576.51 lm

X=0.00m Y=0.00m Z=2.50m

Maximum value : 68.00 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Symmetrical planes

270-90

## Certificates



## Electrical characteristics



# PALMA

Design by Antoni Arola.

## Reference

**3716.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents a wall lamp with two pieces of blown-glass. Its timeless sphere of light evolves towards the organic. Slightly flattened like the shape of the Earth, it gives off a warm and adjustable LED light.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

## Finish




**3716-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3716-93** Matt white lacquer (RAL 9016)

## Sketch



## Electrical characteristics



**Led** 2700K CRI >90 1736 lm 93 lm/W

**Fixture:** 1153.01 lm 49.57 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional DALI**

## Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0818 m<sup>3</sup> /

Gross weight 7.5 kg. / Net weight 5.7 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1153.01 lm

Maximum value : 68.00 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Symmetrical planes  
270-90

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

## Certificates



# PALMA

Design by Antoni Arola.

## Reference

**3718.**

## Application

Wall Lamps

## Installation type

Surface

## Description

Vibia presents a horizontal wall lamp. It is expressed in a different way to the classical globe, new vertical relationships at a large scale combined with vegetation.

## Diffuser

Mat opal triplex blown-glass diffuser

## Materials

Profile: Aluminum

Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)

## Finish




**3718-18** Matt graphite lacquer (ADAPTA RF 9913 WX)



**3718-93** Matt white lacquer (RAL 9016)

## Sketch



## Electrical characteristics



**Led** 2700K CRI >90 2604 lm 93 lm/W

**Fixture:** 1729.52 lm 49.57 lm/W

**Driver included:** CC - Constant Current 500 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional DALI

## Technical characteristics

- Plants not included

## Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.2495 m<sup>3</sup> /

Gross weight 7.7 kg. / Net weight 10.6 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 1

Isolux : Isolux (Floor)

Coordinate system : CG

Light position :

Total flux : 1729.52 lm

X=0.00m Y=0.00m Z=2.50m

Maximum value : 68.00 cd/klm

Light position : C=270.00 G=5.00

Symmetry on the planes : Symmetrical planes

270-90

## Certificates

