



## Product Information Sheet: Hazard Paint & Hazard Paint Anti Slip 2.5L & 5L



**Safety  
Yellow**

While great care is taken with the colour sample shown, no guarantee can be given that it represents exactly the colour offered.

### **TOUGH, GLOSSY, POLYURETHANE FORMULA FOR CONCRETE AND SIMILAR SURFACES.**

Floorsaver Hazard Paint comes in bright yellow which is ideal for internal and external line marking, hatching, highlighting kerbs, step edges, pillars and obstructions throughout the workplace.

- Improve safety indoors and out
- Tough single pack polyurethane
- Easy brush or roller application
- Only one coat is normally needed
- 2.5L covers up to 20m<sup>2</sup> per coat
- 5L covers up to 40m<sup>2</sup> per coat
- Suitable for bare concrete, existing well bonded paint, masonry and most metal surfaces

### **HERE'S HOW TO USE IT:**

#### **Step 1 - Preparation:**

- Surfaces should be clean, dry and dust free.
- If using as a line marker or to paint a kerb or minor obstruction (rather than painting a larger area), the best way of cleaning your floor is probably by using a stiff or wire brush and sweeping away any dust. Grease or oil can be removed by using Floorsaver Cleaner & Degreaser.
- For larger areas of floor – On bare, reasonably clean concrete wash with Floorsaver Floor Etcher - this cleans and keys the surface. On greasy or previously painted floors clean with Floorsaver Cleaner & Degreaser, scraping off any loose paint, dust or dirt. New concrete should be at least 2 months old and always washed with Floorsaver Floor Etcher to reduce alkalinity.

#### **Step 2 – Repairs:**

- Fill small surface holes and cracks using Floorsaver Crack & Hole Filler. Use Floorsaver Mouldable Concrete Filler if you have to repair a step nosing or kerb edge.

#### **Step 3 - Application:**

- Check the surface is dry before painting and that the temperature is a minimum of 15°C.
- Concrete or similar surfaces should be sufficiently porous for the product to 'soak in' to get a key.
- If using a paint brush one coat should be sufficient, but if you are using this over a darker previously painted floor, or applying it by roller, allow for two coats to get a solid colour. Leave for 16 hours (at 15°C - 20°C) before applying the second coat. The second coat must be applied within 5 days of the first coat.
- If using Floorsaver Hazard Paint Anti Slip, tip the small tin of Anti Slip Aggregate into the tin and stir thoroughly using a wooden batten or similar. Use the whole tin of aggregate for the 5L pack size and half for the 2.5L.
- Clean equipment with White Spirit.

### **DRYING TIMES:**

TOUCH DRY 10 hours at 15°C - 20°C.

LIGHT TRAFFIC 24 hours at 15°C - 20°C

FULL USE 36 hours at 15°C - 20°C.

### **SHELF LIFE:**

12 months, if unopened and should not be allowed to freeze.

### **SAFETY:**

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

### **ORDERING:**

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments please email us at [info@floorsaver.co.uk](mailto:info@floorsaver.co.uk)