



Product Information Sheet: Warehouse Linemarking Paint 2.5L



Safety
Yellow

White

While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

TOUGH, GLOSSY, POLYURETHANE LINE MARKER FOR CONCRETE FLOORS.

Floorsaver Warehouse Line Marking Paint is ideal for marking out walkways, or highlighting hazard routes. This single pack, polyurethane line marker can be applied to bare concrete or existing well bonded paint. One coat is generally sufficient if applied using a brush, but a second coat may be required on rough or open textured concrete, or if you are overcoating a darker colour.

- Tough enough for line marking warehouses and workshops
- Single pack – just use as much as you need and replace the lid if you've got any left over
- One coat application (on most surfaces)
- Easily applied by brush
- Use inside or outside
- Suitable for concrete, asphalt when used as a linemarker, wood and most metals
- 2.5L covers up to 20m² per coat, or approximately 150m of 100mm wide line

HERE'S HOW TO USE IT:

Step 1 – Preparation:

- Just make sure the surface is clean and dry. Remove any loose deposits and dirt with a stiff or wire brush. If applying the paint line to a newly painted floor, the new glossy paint should be lightly sanded.

Step 2 – Application:

- Stir the paint thoroughly.
- Do not thin.
- Apply to the floor using a paint brush. Bare concrete should be sufficiently porous to allow the paint to soak in. For particularly porous, open textured concrete, or if you are overcoating a darker colour, a second application may be required.
- Clean equipment with White Spirit.

IMPORTANT:

Do not apply too thickly since this will cause the coating to 'skin over' and slow down the drying process.

DRYING TIMES:

RECOAT (if you need to) 16 hours at 15°C – 20°C.

TOUCH DRY 10 hours at 15°C – 20°C

LIGHT FOOT TRAFFIC 24 hours at 15°C – 20°C

FULL USE 36 hours at 15°C – 20°C. Please check that the paint has fully dried before putting into full use.

WE DON'T RECOMMEND:

- Applying to hard, smooth, very dense or power floated concrete where the paint can't soak into the surface. If in doubt tip a cup of water onto the floor and see if it disappears.
- Applying to concrete contaminated with oil, grease, fats or wax.
- Painting large areas on asphalt – lines and hazard markings are fine.

SHELF LIFE:

12 months, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result. If you have any comments please email us at info@floorsaver.co.uk