

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 10/23/2019 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : CABANA BLUE
Product code : #10432

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Voyageur Soap & Candle Company Ltd. 14 - 19257 Enterprise Way Surrey, B.C. - Canada T 800-758-7773

1.4. Emergency telephone number

Emergency number : INFOTRAC (US & Canada) 1-800-535-5053 | (International) 1-352-323-3500

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2

Skin sensitization, Category 1

H315 Causes skin irritation
H319 Causes serious eye irritation
H317 May cause an allergic skin reaction

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

03/23/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
BENZYL BENZOATE	(CAS-No.) 120-51-4	30 - 70	Acute Tox. 4 (Oral), H302
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	(CAS-No.) 54464-57-2	10 - 30	Skin Irrit. 2, H315 Skin Sens. 1B, H317
LINALYL ACETATE	(CAS-No.) 115-95-7	1 - 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Linalool	(CAS-No.) 78-70-6	1 - 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
ETHYL LINALOOL	(CAS-No.) 10339-55-6	1 - 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319
DIHYDRO MYRCENOL	(CAS-No.) 18479-58-8	1 - 5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Linalyl acetate	(CAS-No.) 115-95-7	< 0.5	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
GERANIOL	(CAS-No.) 106-24-1	< 0.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists:

Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapours/spray.

03/23/2020 EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

GERANIOL (106-24-1)

Not applicable

Linalool (78-70-6)

Not applicable

BENZYL BENZOATE (120-51-4)

Not applicable

DIHYDRO MYRCENOL (18479-58-8)

Not applicable

ETHYL LINALOOL (10339-55-6)

Not applicable

Linalyl acetate (115-95-7)

Not applicable

LINALYL ACETATE (115-95-7)

Not applicable

TIMBERSILK (54464-57-2)

Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

03/23/2020 EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Mixture contains one or more component(s) which have the following colour(s):

Colourless Colourless to light yellow Light yellow to colourless On exposure to air: yellow-brown Colourless to white On exposure to light: turns yellow On exposure to air: turns yellow

White

Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of

overexposure.

Mixture contains one or more component(s) which have the following odour:

Pine odour Floral odour Unpleasant odour Irritating/pungent odour Sweet odour Fruity odour Characteristic odour Almond odour Lemon odour Mild odour Pleasant odour Aromatic odour

Odourless Strong odour

Odor threshold: No data availablepH: No data availableMelting point: Not applicableFreezing point: No data availableBoiling point: No data available

Flash point : $> 100 \, ^{\circ}\text{C}$

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available No data available Relative vapor density at 20 °C Relative density : No data available : No data available Solubility Log Pow No data available Auto-ignition temperature : No data available Decomposition temperature No data available Viscosity, kinematic No data available Viscosity, dynamic No data available **Explosion limits** No data available No data available Explosive properties Oxidizing properties No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

03/23/2020 EN (English US) 4/10

Safety Data Sheet

Viscosity, kinematic

Symptoms/effects after skin contact Symptoms/effects after eye contact

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1	1: Toxic	ological	information
<u> </u>	. II I OAIO	0.0g.0a.	IIII O I I I I I I I I I I I I I I I I

SECTION 11: Toxicological informa	ition	
11.1. Information on toxicological effect	S	
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
GERANIOL (106-24-1)		
LD50 oral rat	3600 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Experimental value, Dermal)	
ATE US (oral)	3600 mg/kg body weight	
Linalool (78-70-6)		
LD50 oral rat	2790 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	5610 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 7 day(s))	
ATE US (oral)	2790 mg/kg body weight	
ATE US (dermal)	5610 mg/kg body weight	
BENZYL BENZOATE (120-51-4)		
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	> 2 ml/kg (Modification of Draize 1959 method, 4 h, Rabbit, Experimental value, Dermal)	
ATE US (oral)	1500 mg/kg body weight	
ATE US (dermal)	4000 mg/kg body weight	
DIHYDRO MYRCENOL (18479-58-8)		
ATE US (oral)	3600 mg/kg body weight	
ETHYL LINALOOL (10339-55-6)		
ATE US (oral)	5000 mg/kg body weight	
TIMBERSILK (54464-57-2)		
LD50 oral rat	>= 5000 mg/kg	
LD50 dermal rat	>= 5000 mg/kg	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitization	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Caroniogoniony	. Not diagoniled	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
STOT-repeated exposure	: Not classified	
Linalool (78-70-6)		
NOAEL (dermal,rat/rabbit,90 days)	250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)	
Aspiration hazard	: Not classified	

03/23/2020 EN (English US) 5/10

: Irritation. May cause an allergic skin reaction.

: No data available

: Eye irritation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 58 / Monday, M	arch 26, 2012 / Rules and Regulations
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
GERANIOL (106-24-1)	
LC50 fish 1	22 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	10.8 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	13.1 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
Linalool (78-70-6)	
LC50 fish 1	27.8 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	59 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	156.7 mg/l (DIN 38412-9, 96 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
BENZYL BENZOATE (120-51-4)	
LC50 fish 1	2.32 mg/l (EU Method C.1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	3.09 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
LINALYL ACETATE (115-95-7)	44
LC50 fish 1	11 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinus carpio)
EC50 Daphnia 1	15 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna)
TIMBERSILK (54464-57-2)	40 00 00
LC50 fish 1	≈ 1.3 mg/l Bluegill Sunfish
EC50 Daphnia 1	≈ 1.38 mg/l Water Flea
ErC50 (algae)	≈ 2.6 mg/l Green Algae
12.2. Persistence and degradability	
GERANIOL (106-24-1)	
Persistence and degradability	Readily biodegradable in water.
Linalool (78-70-6)	
Persistence and degradability	Readily biodegradable in water.
BENZYL BENZOATE (120-51-4)	
Persistence and degradability	Readily biodegradable in water.
DIHYDRO MYRCENOL (18479-58-8)	
Persistence and degradability	Biodegradability in water: no data available.
ETHYL LINALOOL (10339-55-6)	,,
Persistence and degradability	Biodegradability in water: no data available.
ů ,	Discogradability in water. No data available.
LINALYL ACETATE (115-95-7)	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
GERANIOL (106-24-1)	0.0/5
Log Pow	2.6 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Linalool (78-70-6)	
Log Pow	2.84 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

03/23/2020 EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BENZYL BENZOATE (120-51-4)		
BCF fish 1	2.286 (BCFBAF v3.00, Pisces, QSAR)	
Log Pow	3.97 (Experimental value, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
DIHYDRO MYRCENOL (18479-58-8)		
Log Pow	3.47 (Estimated value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
ETHYL LINALOOL (10339-55-6)		
Bioaccumulative potential	No bioaccumulation data available.	
LINALYL ACETATE (115-95-7)		
Log Pow	3.93 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

12.4. Mobility in soil

GERANIOL (106-24-1)	
Log Koc	1.85 (log Koc, PCKOCWIN v1.66, Calculated value)
Ecology - soil	Highly mobile in soil.
Linalool (78-70-6)	
Surface tension	8.3 mN/m (20 °C, ISO 9101: Surface active agents - Determination of interfacial tension)
Ecology - soil	No (test)data on mobility of the substance available.
BENZYL BENZOATE (120-51-4)	
Surface tension	0.027 N/m (210 °C)
Log Koc	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
DIHYDRO MYRCENOL (18479-58-8)	
Ecology - soil	No (test)data on mobility of the substance available.
LINIAL VI AOSTATS (445 OS 7)	
LINALYL ACETATE (115-95-7)	
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3082 Environmentally hazardous substances, liquid, n.o.s. (), 9, III

UN-No.(DOT) : UN3082

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.

Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Packing group (DOT) : III - Minor Danger

03/23/2020 EN (English US) 7/10

Safety Data Sheet

Hazard labels (DOT)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for

solid materials, special provision B54 applies.

: 9 - Class 9 (Miscellaneous dangerous materials)

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 155
DOT Quantity Limitations Passenger aircraft/rail : No limit

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : No limit

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number : 1

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BENZYL

BENZOATE), 9, III

UN-No. (IMDG) : 3082

Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Class (IMDG) : 9 - Miscellaneous dangerous substances and articles

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (BENZYL BENZOATE), 9, III

UN-No. (IATA) : 3082

03/23/2020 EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.

Class (IATA) : 9 - Miscellaneous Dangerous Goods

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

GERANIOL (106-24-1)

Listed on the Canadian DSL (Domestic Substances List)

Linalool (78-70-6)

Listed on the Canadian DSL (Domestic Substances List)

BENZYL BENZOATE (120-51-4)

Listed on the Canadian DSL (Domestic Substances List)

DIHYDRO MYRCENOL (18479-58-8)

Listed on the Canadian DSL (Domestic Substances List)

ETHYL LINALOOL (10339-55-6)

Listed on the Canadian DSL (Domestic Substances List)

Linalyl acetate (115-95-7)

Listed on the Canadian DSL (Domestic Substances List)

LINALYL ACETATE (115-95-7)

Listed on the Canadian DSL (Domestic Substances List)

TIMBERSILK (54464-57-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

03/23/2020 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation

SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

03/23/2020 EN (English US) 10/10