



DATA SHEET

Tellus Power 300 kW DC fast charger

usa.siemens.com/emobility

Features:

- HPC System with 1000VDC
- Powerful Compact All-In-One Charger
- Simple Air-Cooled Power Modules
- Easy to Maintain
- Parallel Charging Feature
- Liquid Cooled Cables
- OCPP 1.6
- Credit Card Reader
- Cord Management

SIEMENS



Tellus Power Green DC fast charger provided by Siemens.



300 kW DC Fast Charging Station

Product Number	US2:HPC3004802
Maximum Power	300 kW
Output Voltage	150 – 1000 VDC
Max Output Current	Up to 500A
Input Voltage Frequency	480V (3P + N + PE) 60 Hz
Input Current Breaker Rating	400A 500A
Power Factor	>0.98
Efficiency	>94% at nominal output power
Connector Options	Dual CCS1
CCS Cable	500A Liquid Cooled
Cycle Mode	1 x 300 kW (Max: 500A)
Parallel Mode	2 x 150 kW (Max: 350A)
Charging Protocol Standards	Mode 4, IEC-61851, ISO-15118, DIN 70121 Mode 4
Connector cable length	CCS - 13 ft (4 m)
Cable Management	Included
Weight	1765 lbs (800 kg)
Dimensions (L x D x H)	41" x 37.4" x 90"
Insulation (input – output)	>2.5 kV
Ingress Protection	NEMA 3S (IP54), IK10
Altitude	<6,600ft (2,000m)
Operating temperature	-30°C to 55°C (-22°F to 131°F)
Working Storage Humidity	≤ 95% RH ≤ 99% RH (Non-condensing)
Display	10" touch screen
Communication Protocol	Ethernet, 4G/WiFi OCPP 1.6J
Access Control	RFID:ISO/IEC 14443A/B Credit Card Reader (Optional)
Metering	DC kWh meter per each connector
Power Electronics Cooling	Air Cooled
Electrical Safety: GFCI	RCD 20 mA Type A
Electrical Safety: Surge Protection	20 kA
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground
Electrical Safety: Output Short	"Output power disabled when output is short circuited"
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics
Emergency Stop	Disables output power with emergency stop button
Regulatory Compliance	UL-2202 CSA C22.2#107.1:2016 EMC: EN 61000-6- 1:2007, EN 61000-6-3:2007/A1:2011/AC:2012

Distributor

Siemens Industry, Inc.
3617 Parkway Ln.
Peachtree Corners, GA 30092
United States of America

Telephone: (855) 950-6339, option 9, or visit
www.usa.siemens.com/createcase
for service.

Article No. SIE-T40061-00-4AUS
© 07.2023, Siemens Industry, Inc.

This document contains a general description of available technical options only and its effectiveness will be subject to specific variables, including field conditions and project parameters. Siemens does not make representations, warranties, or assurances as to the accuracy or completeness of the content contained herein. Siemens reserves the right to modify the technology and product specifications in its sole discretion without advance notice.

