



GENERAL CHAR-ROCK CHARBROILERS

Liquid Propane (LP) / Natural Gas (NG)



MODELS - Liquid Propane (LP) / Natural Gas (NG)

- GCCB-24LP: 2 Burner LP Gas, 24", 70K BTU
- GCCB-36LP: 3 Burner LP Gas, 36", 105K BTU
- GCCB-48LP: 4 Burner LP Gas, 48", 140K BTU
- GCCB-24NG: 2 Burner Natural Gas, 24", 70K BTU
- GCCB-36NG: 3 Burner Natural Gas, 36" 105K BTU
- GCCB-48NG: 4 Burner Natural Gas, 48" 140K BTU

General Countertop Char-Rock Charbroilers give you the ample space needed to grill meats, chicken, fish and vegetables on a bed of stones placed above the burners. The unit evenly distributes the heat toward the food, while the lava rock catches the drippings to create a more flavorful smoke and dramatic flare-up.

FEATURES & CONSTRUCTION

- Durable stainless steel body construction is easy to maintain and allows for a long life span
- Reversible, heavy duty cast iron grilling grates (different grill marks on each side)
- Grates are in individual sections and designed to be tilted for different heating levels
- Manually controlled 35,000 BTU independent burners
- Large burner control dials
- Lava Rock Kit & Holding Rack (accessory included)
- Bottom-mounted drip tray for easy clean up
- Angled sidewalls and bottom plate reflect accurate heat distribution
- Easily monitored gas valve and continuous pilot provide simple, reliable regulation of the gas burner
- Adjustable stainless steel feet for stability
- Back and Side Splashes protect walls and countertops
- ETL approved, units meet all required gas cooking appliance safety standards, codes, and performance regulations



Conforms to ANSI STD Z83.11-2016
Certified to CSA STD 1.8-2016
Conforms to NSF/ANSI Std.4



GENERAL CHAR-ROCK CHARBROILERS

Liquid Propane (LP) / Natural Gas (NG)

- Liquid Propane (LP) or Natural Gas (NG) units available
- Electricity not needed
- Field convertible from LP to NG and vice versa



	GCCB-24 (LP / NG)	GCCB-36 (LP / NG)	GCCB-48 (LP / NG)
# of Burners & BTUs	2 @ 35,000 BTU	3 @ 35,000 BTU	4 @ 35,000 BTU
Total BTU / hr	70,000 BTU / hr	105,000 BTU / hr	140,000 BTU / hr
Hose Connection	.75"	.75"	.75"
in: Dimensions (W x D x H)	24" x 27.6" x 15.2"	36" x 27.6" x 15.2"	48" x 27.6" x 15.2"
mm: Dimensions (W x D x H)	610 x 701 x 386	914 x 701 x 386	1219 x 701 x 386
Product Weight	137 lbs	191 lbs	248 lbs



Intertek
4003027

Intertek
Certified to ANSI NSF Std.4

Conforms to ANSI STD Z83. 11-2016
Certified to CSA STD 1.8-2016
Conforms to NSF/ANSI Std.4

General Char-Rock Charbroilers are warranted for one (1) year from date of installation against defective materials and workmanship.