



ACCESS ROSIN[®]

Innovated & Automated Solvent-less Solutions

5 Spin Flow Vibration - Sieve Tank

Specifications:

- Motor Voltage:** 220V 3P 60Hz
- Motor Power:** 2.25A
- Dimension:** Diameter 30" x 31"
- Tank material:** 316 Stainless Steel
- Thickness:** 0.31"
- Casters:** Shakeproof x 4
- Drain:** 2" Ball Valve
- Isolator:** Damping Springs
- SS316 False Bottom Filter Plate

WHY?

Never Have to Work Your Bags
Continuous Drain for Recirculation Mode.

HOW?

Hash Thrown Rapidly From the Side Walls of
the Sieve Bag for Water to Pass Quickly & Safely.

6 Ice-less Step Down Method

- A.
1. 60° Input Water
 - Storage Tank:** Supports an RO System
 2. 35° Cold Water - Recirculated
 - Additional Tank:** Step Down Temp with Heat Exchanger
 3. 28° Chilled Water
 - Double-Jacket Chilled Tank:** Isolated for Subcool Temp
- B.
1. 60° Input Water
 - Storage Tank:** Supports an RO System
 2. 32° Chilled Water - Recirculate with Heat Exchanger
 - Double-Jacket Chilled Tank:** Isolated for Subcool Temp

7 Warranty & Liability

Warranty Period: 2 Year Limited Warranty
Liability: Access Rosin is not liable for damages
 resulting from improper installation, operation,
 or maintenance.

8 Water Extraction System: PRO SERIES

B. **SMART** Agitator

DIAGRAM

A. **ICE-LESS** System

