



# INDUSTRIAL FLOOR MATS



## DETAILS:

- Size: 119" L x 46" W | 3.02 m L x 1.18 m W
- Thickness:
  - 1/2", 140 lbs | 0.13 m, 63.50 kg
  - 1", 250 lbs | 0.25 m, 113.40 kg
- Applications: Walkway resurfacing, Anti fatigue mats, Compressor shack flooring, Shop flooring & More
- Shipping:
  - 1/2" -  
20 per 4' x 10' x 3' Skid = 2925 lbs | 1327 kg
  - 1" -  
15 per 4' x 10' x 3' Skid = 3380 lbs. | 1533 kg
- Delivery: FOB Legal, Alberta, Canada



## ADVANTAGES:

- They are **strong, tough, and resilient** against a variety of conditions.
- Floor Mats are very easy to take care of.
- It is generally more stain **resistant** than other products.
- Cleaning generally requires no more than the use of a **mop** and warm clean **water**.
- The soft yielding nature of rubber also makes it an appropriate floor for a **variety of areas**.
- Eco-Flex Floor Mats are **nonporous** which means that you don't have to worry about damage from basic liquid spills.
- Floor Mats are **fire resistant**, resistant to burns left from cigarette butts and other small heat sources.
- Made from **100% recycled rubber tires**.



**Champagne Edition Inc. T/A Eco-Flex**  
**Address:** 57425 RR 253, Sturgeon County, AB, Canada T0G 1L1  
**Toll Free:** 1-866-326-3539 | **Direct:** 1-780-961-3229  
**Email:** info@eco-flex.com | **Website:** www.eco-flex.com