



Learn more,
scan here

Power, Innovation & Reliability

The Titan 575 is a titan among truckmounts. It allows you to run two wands, so you can take on those bigger cleaning jobs and you can get done twice as fast. Incorporating the industry's first true water conservation system, it also can be inactive under a full vacuum load for as long as 40 minutes without wasting fresh water. That means you can move furniture or apply pre-conditioners without running to shut off your machine, and your fresh water and recovery tanks need to be filled and emptied less often. Your hot water is used on the job, not dumped into the recovery tank, saving precious fuel each and every day. The Titan 575 was designed for reliability and serviceability; removable magnetic panels make maintenance a cinch. For extreme performance in a compact and reliable package, the Titan 575 has got your back!

Key Features:

- Industry's first Water Conservation System
- 2,000 psi unheated (with optional kit)
- Dual wand capable
- High, consistent working temperatures up to 265°F
- Easy maintenance, high reliability

Standard Equipment

- Runtime hour meter
- Chemical flow meter (0-10 gph)
- Chemical flow control valve
- 5 gallon chemical jug
- Vacuum gauge (0-30" Hg)
- Solution pressure gauge (0-1,500 psi)
- Solution pressure adjustment
- Pre-wired pump-in switch
- Pre-wired APO Switch
- Fresh water inlet
- Water system drain valve
- Stainless steel carpet cleaning wand
- Diverter valve (with ADC heat control)
- Diverter/clutch package for flood work
- Electrical circuit protection
- Pump clutch switch
- Solution temperature control selector
- Two solution outlets
- Solution Hose Length: 100 ft x 1/4"
- Vacuum Hose Length: 100 ft x 2"
- Wand Whip Line: 10 ft 1-1/2"
- 50 ft water supply line
- Recovery Tank: 70 gallon MaxxAir™ recovery tank
- Battery box
- Van installation kit
- Operation & maintenance manual
- Embroidered HydraMaster jacket



Kubota® 32.5 HP Liquid Cooled Engine:

- Keyless electronic ignition
- Exceptionally rigid cast iron block
- 3 cylinder OHV design
- Fuel-efficient technology, 1.7 gph at 300 psi



4007 Dominator™ Tri-Lobe Blower

- HydraMaster exclusive design
- Dual oil bath design with sight level windows
- Durable helical gear drive



High Pressure Pump:

- 2,000 psi unheated pressure
- 4.0 gpm volume
- 1,200 psi heated pressure



Optional Equipment:

- Dura-Flow™ APO (auto pump-out)
- 100 gallon MaxxAir™ recovery tank, aluminum powder coated
- 2,000 psi pressure washing kit
- Thru-floor exhaust kit
- 85 gallon rotomolded fresh water tank
- Evolution Truckmount Wand
- RX-20 rotary carpet extractor

Machine Specifications:

- Dimensions: 26"W x 39"H x 45"D
- Weight: 900 lbs
- Ignition: Electric keyless start
- Chemical System: last-step chemical injection, meter controlled
- Heating System: Tube and fin heat exchanger with ADC temperature control, max. temp. 265°F
- Wand Capacity: Dual
- Fuel Consumption: 1.7 gph
- Uses: Residential and Large Commercial