



## LGR 7000XLi

Portable, high-performance water removal—even at low humidity levels. Reduce and control excess moisture fast with the unit's patented cross-flow technology that optimizes moisture removal in virtually all conditions. Features the new [Command Hub](#), compatible with the new Command Center App. Available now in the [Apple Store](#) and [Google Play Store](#).



## FEATURES

- **Command Center App Users!** For dehu firmware update instructions, visit [Mastering your Dri-Eaz Command Center](#) and scroll down to "Update Your Dri-Eaz Dehumidifier's Command Hub Firmware."
- **Quick Tip:** To connect to the Command Center App to WiFi and enable remote control and monitoring, visit our [FAQ page](#) scroll down to "How to connect Command Center mobile app to WiFi."
- **NEW!** Command Hub touchscreen controller displays real-time temp, RH, grain depression and drying progress trends at a glance. Controller integration product for existing i-Series dehumidifiers also available. [Learn more.](#)
- Advanced Crossflow Technology maximizes efficiency and ensures superior performance in low-grain conditions.
- Fast and convenient access to humidistat, job hours, maintenance reminders and more.
- Process outlet fits 12 in. layflat and rigid ducting.
- Sealed large-capacity pump basin – large enough to contain water from an unintentional defrost after a power outage or other unexpected shut-down.
- Ergonomic design. Handle 2 in. taller for easier use on stairs, folds down for storage. Integrated cord and hose storage.
- Legendary rotomolded housing – practically indestructible – stackable for storage to save space.
- Automatic restart after outage when power is restored.

## SIZES ▪ OPTIONS

- **108110 (F412):** One unit

## SPECIFICATIONS

- **Water removal AHAM (80°F/60%RH):** 130 pts. | 61.5 L / day
- **Max. water removal (saturation):** 235 pts. | 111 L / day
- **Process air (max.):** 325 CFM | 552 CMH. Floor-level outlet.
- **Dimensions (W × H × D):** 20 × 33.5 × 20 in. | 51 × 85 × 51 cm
- **Use weight:** 107 lbs. | 49 kg
- **Amps:** 8.3A
- **Volts:** 115V
- **Frequency:** 60Hz
- **Power cord:** 25 ft. | 7.6 m
- **Drain hose:** 40 ft. | 12.2 m
- **Filter type:** 4-PRO filter
- **Operating range:** 33°F–100°F | 1°C–38°C
- **Housing:** Rotomolded polyethylene
- **Safety:** ETL listed to CSA 22.2 no. 92
- **Xactimate:** WTRDHM>>XL