



Intertek

SMALL APERTURE, MULTI PURPOSE DOWNLIGHT

FEATURES AND BENEFITS:

- Selectable CCT (27 K, 30 K, 35 K, 40 K, 50 K)
- Industry's first Wet Location Rated tilting fixture
- 360-degree rotation, 30-degree tilt
- Quiet optics
- No housing required



CCT Selectable Switch



RETINA PRO



The Retina PRO features 360-degree rotation and 30-degrees of tilt. It offers a sleek design with regressed optics for a quieter ceiling with less glare.

DELIVERED
Up to 850 Im

WHITE (WH) CCT CCT 5 Selectable 27, 30, 35, 40, 50 K

TRIM FINISH



AT AT ALL AND A DAY 2-1/4" Ш 57mm

ACCESSORIES



TL4020 4" PRE-MOUNTING PLATE FOR ROUND TRIM



REDUCTION RING CAN BE PAIRED WITH THE RETINA 4 TO MAKE IT FIT INTO A 5" OR 6" CUT HOLE.



TRIM

С

Round

TLVBE-3 VAPOR BARRIER EXTENDER. FOR USE IN REMODEL. PREVENTS AIR LEAKAGE FROM ENTERING ATTIC

Liteline Corporation Copyright © 2021 All rights reserved.

Telephone 416.996.1856 1.866.730.7704 Fax 905.709.5255 1.888.738.9736

TRENZLIGHTING.COM

M-RETINA4-SS-E REV 11.18.20