

# TL-SLMB4-CCT5

4" OMEGA PRO, CCT Selectable



## Features

### Body

Durable airtight aluminum body with UV stable paint and white PMMA diffuser lens for low glare. Includes silicone gasket for wet location applications. Interchangeable magnetic trim.

### LED Characteristics

This general application light fixture features a 12 watt LED module that maintains intensity producing up to 1030 lumens; with a typical CRI of 90. Available with front facing 5 step CCT switch (2700 K, 3000 K, 3500 K, 4000 K, 5000 K).

### Dimming

100%-10% dimming capability. This fixture is compatible with industry standard TRIAC/ELV dimmers (contact factory for listing of compatible dimmers).

### Beam Spread

The fixture lens provides 75° beam spread.

### Mounting

Includes two spring loaded clips to attach to any ceiling material. The slim profile allows to be mounted under joists or duct work.

### LED Driver

Extruded aluminum hardwire box with 300mA dimmable class II electronic LED driver with 100-135V AC input. Includes an 18" plenum rated FT6 wire with DC 2.1 connector from driver to fixture.

### Quick Connect Push-in Terminals

Three "Quick Connect" push-in terminals for fast and easy wiring.

### Operating Temperature

-40°C~40°C (-40°F~104°F).

### Environment

Suitable for wet locations.  
Suitable for outdoor applications.  
Suitable for insulated ceiling applications.

## Description

4" High performance, easy to install residential grade downlight solution that offers good light output, energy-efficient and streamlined design with interchangeable color trims and CCT selecting switch. Suitable for wet locations.

TECHNICAL DATA	
Application	Ceiling Recess Mount
Approved Location	Wet / Insulated Ceiling
Beam Angle	75°
CCT	2700 K / 3000 K / 3500 K / 4000 K / 5000 K (via CCT switch)
Certification	cETLus
Class II	Yes
Color	White (other accessory colors available)
CRI	90
Dimming	Yes
Dimming Technology	Forward/Reverse phase / TRIAC / ELV
Input	100-135V AC, 60 Hz
Lumens	Up to 1030
Lumens per Watt	Up to 86
Power Factor	>0.9
Projected Lumen Maintenance	70% @ 50,000 hours
Warranty	Lifetime
Wattage	12W

**Notes:** Due to our continued efforts to improve our products, product specifications are subject to change without notice.

