



STEALTH™
HITCHES

THE HITCH MADE TO BE HIDDEN

Operating Instructions

INSERTING ACCESSORIES

1. Insert accessory into the opening until the handle releases, latching the accessory.

Keep hands away from handle, when inserting.



2. NOTE: **YOU MUST PRESS THE LOCK IN TO PREVENT ACCIDENTAL RELEASE!!!**



REMOVING ACCESSORIES

1. Unlock the receiver by inserting the key and turning clockwise 90°. The lock should “pop-out”.



Keys are placed inside stainless steel block for shipping. Remove Rubber Plug to locate your keys.

2. Support the accessory and turn the handle clockwise to release.



The lock and handle are now in position to receive the next accessory.



DO NOT EXCEED MANUFACTURE’S RECOMMENDED VEHICLE WEIGHT CAPACITY

Helpful Hints

- Position hand directly under insertion pin, when inserting into the latch block.



- Do not “slam” the insertion pin, if it doesn’t insert. Slightly move back and forth (while applying force) to center.
- Verify handle is in the “spring-loaded” position before installing the insertion pin. Turn clockwise, if necessary.
- Ensure the latch block is unlocked before attempting to turn the handle.
- As soon as you turn the handle, the accessory will immediately release. Maintain a firm grip.
- Make sure plug (if used) is removed.