

**DIRTY PRO**  
**TOOLS®**

97-105 MONK STREET  
DE223QE

**POWER WASHER**  
**OPERATING & MAINTENANCE**  
**INSTRUCTIONS**

## GETTING TO KNOW YOUR PETROL PRESSURE WASHER



## ASSEMBLY

**NOTE:** Every machine is tested during production, so there may a few drops of water inside the pump assembly.

**FIG. 1**



**FIG. 2**



**FIG. 3**



(Figs. 1.-3):  
The upper handle can only be located in one way.  
Insert the upper handle into the uprights of the lower base and secure in place using the nuts and securing dials provided.

Locate the hose and lance onto the upper frame and secure using the nuts and bolts provided

---

## GENERAL SAFETY RULES

---



**WARNING:** Water at high pressure can be dangerous and can cause damage if the operator is careless. Never allow anyone to operate this pressure washer unless they are familiar with the safety precautions.

---

1. **DO NOT** point the spray at other people, animals, electrical equipment or the machine itself.
2. **DO NOT** hold your finger over the high pressure nozzle.
3. **DO NOT** let children or untrained personnel use this machine.
4. **DO NOT** operate the machine with any of the covers removed.
5. **DO NOT** try to repair this machine. Always refer to your Clarke service department for all repairs.
6. **DO NOT** supply any liquid other than water to the water inlet.
7. **DO NOT** use the detergent pickup facility to introduce flammable liquids/ solvents, e.g. paint thinners, petrol, oil as there is a risk of explosion.
8. **ALWAYS** release the remaining pressure in the system; turn off the water supply and operate the trigger before you remove hoses or accessories.
9. **ALWAYS** keep the machine dry and away from the water spray.
10. **ALWAYS** use protective clothing and safety glasses. Loose particles and other items can be propelled at high speed by the water spray.
11. **ALWAYS** hold the gun securely and expect it to 'kick' when you pull the trigger.
12. **ALWAYS** respect the requirements of the local water company. Pressure washers may only be connected to the mains water supply if a system separator (also known as a backflow preventer) is installed in the supply hose.
13. **ALWAYS** disconnect from the water supply, and make sure that you drain the system when not in use. Keep in a cool dry location.
14. **ONLY** use detergents that are suitable for pressure washers, we recommend that you use CLARKE Traffic Film Remover or CLARKE Wash and WAX (available from your dealer).
15. **WARNING** High pressure water jets can be dangerous, the jet must not be directed at a person or anything that they are wearing.
16. **WARNING** High pressure hoses, fittings and couplings are important for the safety of the machine. Use only hoses, fittings and couplings recommended by the manufacturer.
17. **WARNING** Water that passes through a system separator (also known as a backflow preventer) is not safe to drink.
18. **DO NOT** use the pressure washer if there is damage to the inlet/outlet hose or the machine.

## ASSEMBLY

FIG. 4



TO ASSEMBLE THE WHEELS (Figs. 4.-5):  
Ensure the appliance is kept in the upright position.  
Insert the axle bar into the axle support tube on the lower frame, tighten the bolt to secure in place.



Fit a wheel to the axle and secure using the locking nut provided.  
Repeat this process for each wheel.



**WARNING:**

The engine is not provided with oil. It is necessary to fill the unit before starting the engine.

FIG. 6



ENGINE OIL (FIG. 6 & 7):

**WARNING:**

The engine is not provided with oil. It is necessary to fill the unit before starting the engine. The engine has two oil fill points at the front and back of the engine. Remove the desired cap and fill with the engine oil specified to the upper level mark.  
Replace the oil filler cap.

FIG. 7



FIG. 8



PUMP OIL (FIG. 8 & 10):

**WARNING:**

Must take off this black plastic part out of the pump.

FIG. 9



**WARNING:**

Check the capacity of pump oil and see if it,s reached  $\frac{1}{2}$

FIG. 10



**WARNING:**

Install the red plastic breather parts in this place.


FIG. 11



**HIGH PRESSURE CONNECTION**

(Figs. 11.-14):  
Connect the high pressure hose A to the unit' s high pressure outlet.

FIG. 12



Connect the high pressure hose to the trigger B. Insert the lance C into the trigger. Press firmly against the spring tension and twist the coupling into the locked position. Insert the required nozzle by retracting the coupling at the end of the lance, ensure the nozzle is inserted securely

FIG. 13



INSERTING A NOZZLE (Fig 13):

To insert a nozzle, pull back the locking collar at the end of the lance, insert nozzle and release the collar. This will lock the nozzle in place. Ensure the nozzle is inserted correctly. If not it can fly out and injure personnel or damage property.

FIG. 14



CONNECTING THE HOSE (Fig 14):

Connect the hose to the unit's water inlet connector (Max. 10 bar, max. temperature 40°C) and turn the water on completely.

## OPERATION AND USE

**WARNING:** The engine is not filled with oil. It is necessary to fill the unit before starting the engine. The engine will not produce a spark unless sufficient oil is inside.

**CAUTION:** Do not run the engine with high or low oil level as this can cause engine damage.

**CAUTION:** Only use unleaded gasoline.

**CAUTION:** Avoid damaging your hose by ensuring it does not touch the hot exhaust during and after use.

**CAUTION:** Avoid damaging your pump by ensuring the water supply is clean and free of any foreign objects.

**CAUTION:** Inlet water temperature must not exceed 40°C and 1Mpa

**CAUTION:** Never let the appliance operate for more than 2 minutes with the spray gun in the closed position.

**CAUTION:** Never operate the pressure washer with repeated and rapid on and off movements of the trigger

### WATER SUPPLY FROM THE WATER MAIN

■ Connect a water supply hose (not supplied) to the water inlet connection of the pressure washer.

■ Turn on the water supply and pull the trigger until water is continually flowing out of the nozzle.

### WATER SUPPLIER FROM A CONTAINER

■ Unscrew the coupling part for the water inlet.

■ Screw the suction hose with filter (not included) onto the water connection of the unit.

■ Hang the filter in the container.

■ Vent the unit before operation.

■ Unscrew the high pressure line at the high pressure outlet of the unit.

■ Switch on the unit and let it run until water is free of bubbles at the high pressure outlet.

■ Switch off the unit and screw on the high pressure hose again.

FIG. 15



Pull the trigger to eliminate trapped air and wait for a steady flow of water to emerge from the spray nozzle.

#### NOTE:

In order to assist the first startup it is recommended to press the trigger during the pulling of the starter handle.

FIG. 16



To prevent accidental operation the trigger is fitted with a locking facility.

## OPERATION AND USE

FIG. 17



**STARTING THE ENGINE**  
(FIG. 17-20):  
Push the fuel lever A to the right (On position).

FIG. 18



Push the choke lever B to the left; closing the choke for initial start-up.  
**NOTE:** Do not use the choke if the engine or air temperature is warm.

FIG. 19



Turn the engine switch clockwise to the ON position.

FIG. 20



Pull the black starting rope handle gradually until you feel resistance; then make a rapid pull.  
**NOTE:** Return the starting rope handle gently to prevent damage to the starter assembly.  
Do not pull the rope all the way out as this can damage the starter assembly.

FIG. 21



Let the engine idle for a short while to preheat before pushing the choke lever C to the right.

FIG. 22



When the appliance is in operation, the speed can be adjusted by moving the throttle D control lever to the high position (indicated by a hare).  
**NOTE:** There is a stop bracket on the throttle control lever; do not force this bracket as it can damage the engine.

FIG. 23



**STOPPING THE ENGINE**  
(Fig 23-24):  
In an emergency turn the engine switch anticlockwise to the OFF position to stall the engine. To stop the appliance normally use the following sequence.

FIG. 24



Turn the engine switch anticlockwise to the OFF position. Then slide the fuel lever E to the right; OFF position.  
**CAUTION:** When you have finished working turn off the engine. When the machine is switched off, always discharge the pressure by pressing the trigger.

## OPERATION AND USE

### ADJUSTING THE SPRAY PATTERN (Fig.25)

You have the choice of 4 different colour coded nozzles giving you different spray patterns to choose from:

#### **0° nozzle (Red):**

This nozzle delivers a pinpoint stream and is extremely powerful.

It covers a very small area of cleaning. This nozzle

should only be used on surface that can withstand this high pressure such as metal or concrete. Do not use on wood.

#### **15° nozzle (Yellow):**

This nozzle delivers a powerful 5 degree spray pattern for intense cleaning of small areas. This nozzle should only be used on areas that can withstand the high pressure from this nozzle.

#### **40° nozzle (White):**

This nozzle delivers a 40 degree spray pattern and a less powerful stream of water. It covers a wide area of cleaning. This nozzle should be used for most general cleaning jobs.

#### **Low pressure nozzle (Black):**

This nozzle is used to apply chemicals or cleaning solutions. It has the least power stream.

FIG. 25



#### **NOTE:**

Before using the pressure washer to clean patio paving slabs it is advisable to test a small area first, some paving slabs are manufactured from inferior materials and the use of a pressure washer could damage the surface.

### USING THE DETERGENT FACILITY (Fig. 26)

Fill a suitable container with pressure water detergent. Do not use washing up liquid as it contains salt. We recommend the use of good quality pressure washer detergent for use with this pressure washer. Please follow the instructions on the container.

Most automobile detergents are a combination of a detergent and a wax solution.

The viscosity (thickness) of the detergent will increase in cold weather. It is recommended that this type of detergent is diluted with water before filling the container. When using combination wash and wax solutions we recommend that they are diluted before use. As a general guide we would recommend a dilution rate of 50/50. However a trial and error process would determine the ideal dilution rate for a particular detergent.

#### **NOTES:**

A thick viscous detergent would not flow freely from the detergent tank and the residue would cause a blockage flow system. After using the detergent facility it should be flushed thoroughly using copious amount of water. To activate detergent delivery, fit the Black LOW PRESSURE nozzle to the end of the lance. Submerge the end of the detergent pick up pipe into your container of pressure water detergent. Suction and mixing will occur automatically as the water flows through the pump.

FIG. 26



FIG. 27




### CLEARING A BLOCKAGE (Fig. 27)

If at any time the flow rate stutters or is inconsistent, release the trigger and switch "OFF" the machine. Squeeze the trigger to relieve any pressure and check the jet in the end of the lance for any blockage. If a blockage is suspected use some wire to clean the inside of the nozzle.

## OPERATION AND USE

### SAFETY INSTRUCTIONS FOR THE ENGINE

- Before operating the engine, be sure to read all instructions carefully as injury or permanent damage to equipment may occur.
- Run the engine in a well ventilated area.
- Ensure the appliance is at least one metre away from building walls or other equipment.
- Keep the appliance away from flammable liquids such as petrol.
- Refuel in a well ventilated area with the engine switched off and avoid sparks or naked flames.
- When refuelling ensure that you do not overfill the fuel tank.
- If any fuel is spilled ensure it is cleaned up thoroughly before restarting.
- Ensure the fuel cap is located securely.
- The exhaust mufflers get very hot and will remain hot for sometime after the engine is switched off.
- Ensure the appliance is cooled before transporting or storing.



### PRE-OPERATION INSPECTION

#### ⚠CAUTION:

Engine oil is a key factor in deciding the engine's performance. Do not use engine oil with additives or 2-stroke gasoline engine oil, as they do not have enough lubricating properties, which may shorten the engine's service life.

- Check the engine is on level ground.
- SAE 30 is recommended for general all temperature use.
- Remove the dipstick and clean it.
- Reinsert the dipstick into the oil filler without screwing it in and check the oil level.
- If the oil level is too low add the required amount of engine oil to the oil filler mark.
- Replace the dipstick securely.

#### ⚠CAUTION:

Running with insufficient engine oil may damage the engine severely.

FIG. 28





## OPERATION AND USE

### FUEL AND FUEL TANK:

Only use unleaded petrol or fuel with an octane number over 86. Using unleaded petrol or fuel will decrease the possibility of producing carbon deposit and prolong the engines service life. Never use old or polluted petrol or fuel or a mixture of petrol and engine oil. Make sure the fuel is free of dirt and water.

### ⚠ CAUTION:

Handle fuel with care because it can damage plastic and painted surfaces.

Remove the fuel filler cap and check the fuel level. If the fuel lever is too low, refuel the tank. Remember when adding fuel do not fill over the fuel filter shoulder.

### WARNING:

Petrol is extremely flammable and is explosive under certain conditions. Refuel in a well ventilated area with the engine stopped. Do not smoke or allow flames and sparks in the area where petrol is stored or where the fuel tank is refuelled. After refuelling make sure the fuel cap is returned securely. Be careful not to spill fuel when refuelling. Spilled fuel or fuel vapour may ignite. If any fuel is spilled make sure the area is dry before starting the engine.

### FUEL TANK FILTER (Fig.29):

After every 150 hours of running or every three months the fuel tank filter should be removed and cleaned. Remove the fuel tank filler cap and the filter, clean the filter thoroughly using environmentally friendly water based degreasing agent and re-fit.

### OIL LEVEL SWITCH:

The engine oil alarm is designed to prevent the operator starting the engine when the oil in the crankcase is insufficient.

Running with insufficient oil will damage the engine. Once the oil level in the crankcase is too low, the engine oil alarm will stall the engine automatically to avoid damage while the engine switch is still ON.

FIG. 29



FIG. 30



### AIR FILTER (Fig.30):

After every 100 hours of running or every month, the air filter should be removed and examined for deterioration and cleaned. Clean the air filter thoroughly using environmentally friendly water based degreasing agent. Allow to dry fully then replace the air filter. Never run the engine without the air filter fitted.

### STORAGE:

If the engine is not to be used or is to be stored for more than one month the following storage procedure should be carried out.

- Drain all the fuel from the fuel tank and the carburettor ensure that all the fuel has been removed.
- Remove the spark plug and pour approximately one tablespoon full of clean engine oil into the spark plug hole.
- With the ignition turned OFF gently pull on the recoil starter cord several times.
- Re-fit the spark plug and continue to pull the recoil starter cord until the piston is on the compression stroke (when resistance is felt) then stop pulling.
- Store the pressure washer in a dry well ventilated place under a cover to prevent any dust or debris from accumulating on the pressure washer.

### WINTER AND LONG TERM STORAGE:

If the pressure washer is not to be used for more than 3 months or if there is a danger of ice or frost during winter months the pump unit will require protection to prevent seizing and damage caused by freezing.

## **MAINTENANCE**

### **EXHAUST CONTROL SYSTEM**

With the engine running, carbon monoxide, nitrogen oxide and hydrocarbon are produced, and in certain conditions nitrogen oxide and hydrocarbon will react together to make smoke while carbon monoxide is toxic, so exhaust control is very important. The manufacturer decreases exhaust emissions by introducing poor-fuel carburetors and other devices to solve the problem. To keep the exhaust of your engine within the standard exhaust emission values, pay attention to the following:

#### **MAINTENANCE**

Maintain the engine periodically in accordance with the maintenance schedule. The maintenance schedule is made out on the basis of normal use in normal conditions. If using under heavy load, dusty or wet conditions or in high temperature, more frequent maintenance will be necessary.

#### **REPLACEMENT OF PARTS**

We recommend that you use parts that are supplied by the manufacturer or equivalent quality parts. Replacement parts of inferior quality may impair the effectiveness of the exhaust control system.

#### **MODIFYING**

Modifying the exhaust control system may make exhaust emissions exceed statutory limits. Illegal modifications are:

- Dismantling or modifying any part of the air inlet or outlet system.
- Modifying or removing speed adjustment controls or connections which may result in the engine running outside its set parameters.

#### **PROBLEMS AFFECTING EXHAUST EMISSIONS**

- Difficulty in starting or stopping.
- Erratic idling.
- Giving off black smoke or excessive fuel consumption.
- Poor ignition spark or no spark.
- Ignition too advanced. If you have any of these above problems please contact your dealer.

#### **CAUTION:**

Before carrying out any maintenance to the machine release any pressure and remove the water connection.

#### **WATER SUCTION FILTER CHECKING**

Check periodically in order to avoid deposits clogging it.

#### **SPARK PLUG MAINTENANCE**

After every 50 hours clean the spark plug with a brush. If the insulator on the spark plug is damaged replace it immediately. Check the spark plug gap with a feeler gauge, the gap should be 0.7 - 0.8mm. If adjustment is necessary bend the side electrode carefully.

Check the spark plug gasket is in good condition or replace with a new one. Screw in the spark plug to the bottom first by hand and then tighten by using a spark plug wrench. If a new spark plug is used, twist a  $\lambda$  more turn after impacting the gasket. If using the original one twist  $\frac{1}{4}$  -  $\frac{3}{4}$  more turn.

#### **CAUTION:**

The spark plug eliminator should be serviced at least once every 100 hours of operation so as to keep it in good condition.

#### **WARNING:**

The muffler is very hot during running the engine and for a prolonged period after stopping. Only service after the engine cools down completely.

Unscrew two nuts and remove the exhaust elbow from the engine body.

Unscrew five screws from the muffler guard and take it out.

Unscrew from the spark plug eliminator and separate from the muffler.

Clean the spark eliminator mesh with a wire brush.

Reinstall the spark eliminator in reverse order of removal.

#### **CAUTION:**

Be careful not to damage the spark eliminator. Never use a damaged spark eliminator.

#### **CARBURETTOR IDLING ADJUSTMENT:**

Start and pre-heat the engine until it reaches normal working temperature.

Obtain standard idling by adjusting the throttle fixing screw under the engine,

Standard idling: 3400 $\pm$ 300rpm.

## MAINTENANCE



### TRANSPORT

Transport with the fuel switch in the off position. Ensure the engine is cooled so as to avoid the risk of burns or fire.

### CAUTION:

Do not tilt the engine to avoid spilling fuel. Spilled fuel or fuel vapour may ignite.

### STORAGE

If the engine is not to be used for a long period of time ensure it is stored correctly. Make sure the storage area is dry and free of dust.

### PREPARE FOR STORAGE

Disconnect the spark plug. Put a spoonful of fresh engine oil into the cylinder and rotate the engine to distribute the oil evenly. Replace the spark plug.

Pull the starting rope until you feel resistance and then keep pulling so as to align the arrow of the starting sleeve with the hole of the starter. This will close both the inlet and outlet valves to help prevent the engine rusting inside.

Cover the engine to keep it free of dust.

### REMOVAL FROM STORAGE

Before re-using, service the engine in accordance with the instructions in the following table.



STORAGE TIME	SERVICE ITEM
Within one month	No service needed
One - Two months	Drain out original fuel of the fuel tank and refuel
Two months - One year	Drain out original fuel of the fuel tank and refuel
	Drain out the fuel in the carburettor 1
	Empty the deposit cup 2
Above One year	Drain out original fuel of the fuel tank and refuel
	Drain out the fuel in the carburettor 1
	Empty the deposit cup 2
	Move the engine from the storage place, and start up

1 Unscrew the drain plug and drain out the fuel in the carburettor:

2 Turn off the engine switch first, disconnect the deposit cup and empty it.

### NOTE:

Do not dump oil containers or discarded engine oil into the ground. For environmental protection take discarded engine oil in a closed container to a recycling station.

### WARNING:

Fuel is extremely flammable and explosive under certain conditions. Keep cigarettes, naked flames and sparks away from operating site.

## MAINTENANCE

To keep the engine in sound condition, the user should maintain it according to the table below.

### CAUTION:

Use parts that are supplied by the manufacturer, otherwise damage to the engine may occur.

### WARNING:

Stop the engine before servicing. If servicing is required with the engine running ensure there is good ventilation in the area. Exhaust emissions contain toxic carbon monoxide which may cause injury or be fatal if inhaled.

### ENGINE OIL REPLACEMENT

Place the machine on a level surface and warm up the engine for several minutes. Then stop the engine.

Remove the oil filler cap

Place an oil pan under the engine. Remove the oil drain plug so that the oil can be completely drained. You will need to use a tube or other similar device to prevent the oil leaking onto the frame of the pressure washer.

Check the oil drain plug, gasket oil filler cap and O-ring and if damaged replace.

Reinstall the oil drain plug.

Add engine oil up to the upper level of the dipstick.

### NOTE:

Do not dump oil containers or discard engine oil into rubbish boxes or into the ground. For environmental protection take discarded engine oil in a closed container to a recycling station.

### NOTES:

\* Only for inside ventilating double-core carburetors.

\*\*Only for paper core air cleaners.

1. More often than in schedule if used in dusty conditions

2. Items to be done by dealer unless you are fully trained and equipped to do so.

Item		Each time	First month or 20 hours	Each month or 50 hours	Each 6 months or 100 hours	Each year or 300 hours
Engine oil	Oil level check	✓				
	Replace		✓		✓	
Reduction gear oil	Oil level check	✓				
	Replace		✓			
Clean	Check	✓				
	Air cleaner			✓	✓*	
	Replace					✓
Deposit cup	Clean				✓	
Spark plug	Clean, adjust				✓	
	Replace					✓
Spark eliminator	Clean				✓	
Idling	Clean, adjust					✓ <sub>2</sub>
Valve clearance	Clean, adjust					✓ <sub>2</sub>
Fuel tank & fuel filter	Clean					✓ <sub>2</sub>
Fuel supply line	Check					

### PUMP NOTICE

- For the convenience of transport, Pump without machine oil, and breather plug is not installed. Please add 15W/40 or 30 machine oil before using. Machine oil quantity is subject to slightly not too oil lens center line, then install the breather plug.
- After using 20 hours of the new machine, pour the machine oil out, and add the appropriate amount of kerosene, fuel is according to standard a little than oil lens center line. Operate the pump without load in 10-15 seconds, then close the machine and pour out the kerosene, add the new oil.
- Please check the oil mass before using. If the oil level is less than 1/2 oil lens, it's needs to add the oil to the oil lens center line.
- Accumulative use after 100 hours, change the oil in the same way. And every 100 hours to change the oil. It's very important to Extend the service life of the pump,

## TROUBLESHOOTING


### PUMP TROUBLESHOOTING

TROUBLE	PROBABLE CAUSE	REMEDY
Fluctuating pressure	Pump sucking in air	Check connection are tight
	Valves dirty, worn out or seized	Contact customer helpline
	Blocked jet	Remove blockage using jet cleaning tool
Water leakage from pump	Seals worn out	Contact customer helpline
The pump does not reach the required pressure	Pump sucking in air from connections or hose	Check tightness of all connections
	Suction/delivery valves are clogged	Clear or replace valves. Have machine checked by Service Centre
	Unload valves are stuck	Loosen and re-tighten regulating screw
	Lance or nozzle worn out	Check and/or replace
Pump is running but no water delivery	Kinked inlet and or pressure hose	Check, straighten and replace if required
	Blocked inlet filter	Remove and clean filter
	Blocked jet	Remove blockage using the jet cleaning tool

### ENGINE TROUBLESHOOTING

FAULT	PROBABLE CAUSE		REPAIR			
Engine won't start	Insufficient compression	Loose spark plug	Tighten plug			
		Loose cylinder head bolt	Tighten bolt			
		Damaged gasket	Replace gasket			
Engine won't start	Sufficient compression	<b>FUEL SYSTEM PROBLEMS</b>				
		No fuel supplied to combustion chamber	Insufficient pulling speed for starting rope	Pull rope sharply		
			Foreign matter in fuel tank	Clean tank		
			Clogged fuel line	Clean fuel line with dealers advice		
			No fuel in tank	Supply fuel		
			Fuel tap not open	Open tap		
Low engine output	Sufficient compression	<b>FUEL SYSTEM PROBLEMS</b>				
		Combustion chamber supplied with fuel	Poor spark	Spark plug dirty with carbon or wet with fuel Remove carbon or dry spark plug		
			Good spark	Damaged spark plug	Replace spark plug	
				Faulty magneto	Consult dealer	
		Engine runs erratically	Sufficient compression	Combustion chamber supplied with fuel	Improper adjustment of carburetor	Consult dealer
					Good spark	Insufficient pulling speed for starting rope
<b>FUEL SYSTEM PROBLEMS</b>						
Engine runs erratically	Sufficient compression	Wrong grade of fuel used		Check grade of fuel		
		Overloaded		Check the working conditions		
		Overheating				

## PUMP PARTS DRAWING



No	name	QTY	No	name	QTY	No	name	QTY
1	Oil seal	1	30	valve plank	3	59	ball	1
2	flange plate	1	31	valve spring	6	60	valve seat	1
3	51108-F bearing(loose)	1	32	valve washer	6	61	spring	1
4	51109-F bearing	1	33	valve base	6	62	nozzle	1
5	51110-F bearing(close)	1	34	O-ring	6	63	O-ring	1
6	steel lagging	1	35	pump head	1	64	nipple	1
7	O-ring	1	36	temperature control valve	1	65	O-ring	1
8	cam	1	37	oil cap washer	4	66	nut	1
9	51108-E(loose)	1	38	screw	4	67	nut	1
10	51109-E bearing	1	39	O-ring	1	68	spring	1
11	51110-E(close)	1	40	inlet pipe	1	69	washer	1
12	spring plate	3	41	gasket	1	70	O-ring	1
13	piston spring	3	42	ring nut	1	71	vale cap	1
14	piston	3	43	ring nut	1	72	O-ring	1
15	O-ring	1	44	valve plank	3	73	uncork ring 1	1
16	pump crankcase	1	45	O-ring	4	74	O-ring	1
17	O-ring	1	46	plug2	1	75	valve	1
18	oil plug seat	1	47	O-ring	1	76	valve spring	1
19	oil plug cover	1	48	pump body	1	77	pin	1
20	oil seal	3	49	spring	1	78	O-ring	1
21	assistant water seal mat	3	50	ball	1	79	uncork ring 2	1
22	assistant water seal	3	51	O-ring	1	80	top seat	1
23	pilot seat	3	52	O-ring	1	81	O-ring	1
24	O-ring	3	53	connector	1	82	ball	1
25	main water seal mat	3	54	oil cap washer	7	83	base	1
26	main water seal	3	55	screw	7	84	plug1	1
27	water seal washer	3	56	O-ring	1	85	u-plug	1
28	bilging valve bonnet	3	57	valve	1	86		
29	O-ring	3	58	O-ring	1	87		

## DECLARATION OF CONFORMITY



### DECLARATION OF CONFORMITY

This is an important document and should be retained.

We hereby declare that this product(s) complies with the following directive(s):

**Product Description:** Petrol Power Washer

**Date of Issue:** 04.05.2017

**Conformity Assessment Procedure:** to 2000/14/EC Annex V

**Manufacturer:** Dirty Pro Tools

**Noise Related Value:** 420 l/h

**Measured Sound Power Level:** 107dB

**Guaranteed Sound Power Level:** 109dB

We hereby declare that this product(s) complies with the following directive(s):

2004/108/EC Electromagnetic Compatibility Directive.

2006/42/EC Machinery Directive.

2000/14/EC Noise Emission Directive, (amended by 2005/88/EC)

87/88/EC Emission of Gaseous and Particulate Pollutants for Internal Combustion Engines to be installed in Non-road Mobile Machinery, (amended by 2010/26/EU)

The following standards have been applied to the product(s):

EN 58012:2007 +A1:2009, EN 60335-1:2007, EN 60335-1:2012, EN 60335-2-79:2012,

EN ISO 12100:2010.

The technical documentation required to demonstrate that the product(s) meet(s) the requirement(s) of the aforementioned directive(s) has been compiled and is available for inspection by the relevant enforcement authorities.

Signed: