

Natural NR/SBR

SPECIFICATION SHEET

Grade	No8	
Colour	BLACK	
Elastomer	NR/SBR	
Quality	ELECTRICALLY TESTED 15KV WORKING VOLTAGE 650V FINE FLUTED	
Hardness Shore A ± 5	70°	ISO 7619-1
SG (g/cm²)	1.5	ISO 2781
Tensile (N/mm²)	3.5	ISO 37
Elongation %	300	ISO 37
Compression %		ISO 37
Tear Strength	20	ISO 34-1
Abrasion mm³	200	ISO 37
Temperature (° C) from		
Temperature (°C) to		

Roll Tolerances

Width tolerance:	+/- 2%	ISO 3302 SW1
Length tolerance:	+/- 2%	ISO 3302 SW1

Thicknesses available

9.5mm	.914m, 1m, 1.22m	●
-------	------------------	---

Thickness

0.5– 1mm	+/- 0.2mm
1.5mm –3mm	+/- 0.3mm
4mm—5mm	+/- 0.4mm
6mm	+/- 0.5mm
8mm	+/- 0.7mm
10mm—15mm	+/- 1mm
20mm	+/- 1.4mm
25mm	+/- 1.75mm

● Items listed above usually ex stock.

Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application. Advice is available but final responsibility remains with the customer.