

## **1. GENERAL DESCRIPTION**

Product Name:TSEC633Chemical Family:Chemically Cross linked Polyethylene Foam

## 2. COMPOSITION / INGREDIENT DATA

<u>Substance</u>	<u>Substance</u>		
(Abbreviation)	<u>(Chemical Name</u> )	Cas#	<u>PHR</u>
LDPE	Polyethylene	9002-88-4	100
DCP	Dicumylperoxide	80-43-3	<1
ADCA	Azodicarbonamide	123-77-3	<20
MB	Pigment		< 1
DBSPE	Ethane -1,2-	84852-53-9	<18
	bis (pentabromophenyl)		
Sb2 O3	Antimony Trioxide	1309-64-4	<8

# **3. HAZARD IDENTIFICATION**

### **Most important Hazards:**

Contains Antimony trioxide.

ACGIH consider Antimony trioxide as A2- suspected human carcinogen.

Antimony trioxide is according to directive 67/458/EEC classified as Xn – harmful, Class 3 – carcinogen, R40 – limited evidence of carcinogenic effect.

However for encapsulated or bound preparations (eg polymers/elastomers/ extruded form) the exposure path and therefore the risk is eliminated. According to Article 10 or Annex VB9 (EU Dangerous Substance Directive, 67/548/EEC, Annex VI, 9.3) such preparations "do not

present a danger to human health by inhalation, ingestion or contact with the skin or to the aquatic environment in the form in which they are placed on the market"

## **4. FIRST AID MEASURES**

**Ingestion:** If there is any suspicion that the material has been ingested, seek immediate medical attention. If only a few granules have been swallowed, rinse the mouth with cold water. In this case there is no real danger

Skin Contact: There is no risk and no need to work with gloves.

**Eye Contact:** Rinse eyes with water. In case of an uncomfortable sensation, consult a doctor or ophthalmologist.

## **5. FIRE FIGHTING MEASURES**

### Suitable extinguishing media: CO2, H2O, Foam, Dry Chemical Powder

During a fire it is advisable to cool the material with water. Material that was not ignited should, if possible, be removed from the vicinity of the fire to a safe area. Care must be taken not to stand underneath burning material, dripping of burning molten material may occur.

Smoke may contain toxic substances; it is therefore advisable to wear a mask.

Even after the flames have been extinguished, the material should be cooled with water, in order to prevent a renewed outbreak of the fire due to self-ignition.

### **6. ACCIDENTAL RELEASE MEASURES**

Personal Precautions:See Section 8Environmental Precautions:None necessary

**Methods for Cleaning Up:** Can be cleaned by any acceptable method: Dust and fragments may be vacuumed, swept or blown away by use of air pressure.

### 7. HANDLING AND STORAGE

### Handling: No Restrictions

**Storage:** It is advisable to store in a ventilated warehouse on pallets raised off the ground. The material should not be stored outside, particularly in the rain or in the sun. Shrink wrap is not advisable.

# **8. EXPOSURE CONTROL / PERSONAL PROTECTION**

Chemical Name	<u>CAS No.</u>	<u>TLV/TWA</u>	
Antimony trioxide DBDPE	1309-64-4 84852-53-9	0.5 (mg/m3) TLV not determined	ACGIH
		TWA 5 (mg/m3)	IAHA

#### Engineering measures to reduce exposure:

If dust or vapor condition is above the recommended level, use local extractionapparatus (likely only in the case of a fire).

#### Personal Protection Equipment:

Respiratory Protection:	Not necessary.
Hand Protection:	Not necessary.
Eye Protection:	Not necessary.
Skin and Body Protection:	There is no need for any protective measures.
Hygiene:	Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or
	smoking.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

State: Foam PE	Colour: Various	Odour: None
<b>Density:</b> 25-250kg/m3	Melting Point: N/A	Decomposition Temp: >300oC
<b>Boiling Point:</b> N/A	Vapour Pressure:N/A	Auto Ingnition Temp:N/A
Flashpoint:N/A	Explosion Risk:N/A	Water Solubility: None

### **10. STABILITY AND REACTIVITY**

Stability:	(x) Stable	( ) Unstable	
Conditions to avoid:	Temperatures over 1500C		
Hazardous Decomposition	on		
products:	COx, Hydrocarbons, Trace Ammonia		
Hazardous Polymerization:	( ) may occur	(x) will not occur	

#### **11. TOXICOLOGICAL INFORMATION**

Acute toxicity:LD50 (mg/kg)			
Component:	Antimony	84852-53-9	
Oral (rat)	>3000	>2000	
Skin:	No toxicity		
Eye:	Dust may cause irrita	ation	
Ingestion:	Uncomfortable if swallowed in large quantities		
Inhalation:	A high concentration of dust and fragments may cause nausea.		
Chronic toxicity: Antimonjy trioxide is considered by ACGIH as AS – suspected human			
carcinogen. Antimony trioxide is accordingly to directive 67/458/EEC classified as Xn, Class			

3, R40. The Antimony trioxide is incorporated in the material matrix thus the exposure path and therefore the risk is eliminated.

# **12. ECOLOGICAL INFORMATION.**

**Details for elimination:** The waste can be buried at an appropriate site or burned in a furnace. The foam can also be grounddown for the production of recycled foams.

Performance in Ecological Sub System: PE is regarded as biologically inert.

Ecotoxicity: Antimony trioxide – N/A 84852-53-9 LC50 48H (Orange red-killifish) > 500 mg/I

## **13. DISPOSAL CONSIDERATIONS:**

Waste from residues/unused:	Dispose of in accordance with local regulations.
Contaminated Packaging:	Dispose of in accordance with local regulations.

# **14. TRANSPORTATION INFORMATION:**

ADR/RID-HI/UN No.:	Not classified	Class:
Proper shipping name:		
IMDG-UN No.: None	Marine Pollutant: No	Class:
Proper shipping name:		
MFAG:	MDG Page:	EMS:
ICAO:	UNI/ID No.:	Class:
Proper shipping name:		

# **15. REGULATORY INFORMATION**

Classification according to European directive on classification of hazardous preparations 91/155/EEC Symbols: R-phrases: S-phrases:

Unit 8 Patches Yard, Cavendish Lane, Glemsford, Sudbury, Suffolk CO10 7PZ

Tel: 01787 827070

Sales@sealextrusions.co.uk