

Roof Waterproofer 5KG



If you want to avoid costly re-roofing, or get a few more years out of your garage or shed roof before it really starts to deteriorate, then Roof Waterproofer is the product for you.

- + Cost effective waterproofer – no high bills and hidden extras
- + Don't let your roof be 'out of sight, out of mind'
- + Prevention is better (and far cheaper) than cure
- + Flexible – doesn't crack or split
- + Can be applied in the rain for emergency repairs
- + Really easy to apply

Why

Weatherproof your roof against the elements by using Roof Waterproofer, the easy, most cost effective way to refurbish or repair roofs. It's a flexible, strong, bitumen and fibre based waterproofer that not only protects and preserves your roof, it extends the life of it too. Roof Waterproofer is black but weathers down to grey over a period of time. It resists both water and direct sunlight and doesn't crack or split. It is effective on most types of roof, including tiled, concrete, corrugated iron and felt. We particularly recommend it for flat roofs and sheds. For outdoor use only.

Prepare It

You can apply Roof Waterproofer when it's pouring with rain in an emergency. For long term repairs the surface should be as dry as possible. Remove dirt, moss and other loose material with a wire brush. A fungicide may be used where applicable.

Apply It

Load the brush generously and apply 1m² per kilo of Roof Waterproofer. If you need a second coat then apply it at right angles to the first one. Don't brush out to a thin film – the idea here is to apply a good thick coating.

Tip – for larger splits and cracks, apply a coat of Roof Waterproofer, then mix some dry sand with more Roof Waterproofer to produce a mortar which can be applied with a trowel.

Cover It

Covers approximately 5m² per 5kg container.

Clean It

Clean applicators with White Spirit before the product sets.

You'll need

5" paint brush

This product is available on our website and can be shipped with your order for Roof Waterproofer so you can get the job done quickly.

Dry It

After about 24 hours a surface skin forms. Once all moisture has evaporated then setting begins.

Important...

Do not apply to bare wood in order to form a seal, as trapped moisture can cause blistering on porous surfaces in warm weather. During the wet, only temporary emergency repairs can be provided by Roof Waterproofer.

Do not use on EPDM rubber roofs. Test on a small area if in doubt about product suitability.

Store It

The shelf life of Roof Waterproofer, if unopened, is one year. Do not allow to freeze.

Disposal and Safety information

Please see the *Material Safety Data Sheet* at www.paintpeople.co.uk for safety information.

Volatile Organic Compounds

EU limit value for this product (Cat A/i): 500g/L (2010). The product contains 410g/L VOC.

Availability

Roof Waterproofer is supplied in 5kg containers. Available from www.paintpeople.co.uk