

Seal 'n' Tint 5L



If you want to give your dull, drab, grey concrete or old paving slabs a new lease of life, without putting a solid coat of paint over the top, then Seal 'n' Tint is for you!

- + Transforms drab concrete or paving slabs
- + Requires minimal preparation
- + Is easy to apply with a brush or roller
- + Long lasting
- + Stops concrete from dusting
- + Solvent free, no smell during application
- + Use indoors or outdoors

Why

Seal 'n' Tint isn't a paint – it's a bit different. Seal 'n' Tint is a penetrative, water based tinted sealer, which enhances the look of concrete rather than disguising it.

So if you've got a driveway, path, patio, basement, garage or cellar which need a bit of sprucing up, just apply one or two coats of Seal 'n' Tint. You will be left with a dust free, coloured, low sheen finish, which is easy to keep clean and looks good.

Prepare It

There's not much preparation to do. If your floor is clean, dry and free from any loose material, just give it a good sweep and you're good to go. If there's any grease or oil present, treat it with our Oil & Grease Remover.

Seal 'n' Tint is designed for porous surfaces, so if your concrete or paving slabs have been painted or sealed, then you will need to remove it all first. If your floor is very porous, it's best not to wash it before applying Seal 'n' Tint, since it will absorb too much water. Seal 'n' Tint should ideally be applied to a completely dry surface, however some slight dampness from cleaning is not a problem.

Apply It

Making sure the lid is on tight, give the tin a good shake.

Apply in dry, warm (above 10°C) conditions. Good ventilation helps the product to dry. Pour some into a roller tray. Don't pour directly onto your concrete as this may create a patchy effect. Using a medium pile roller apply sparingly to make sure you are achieving the desired result. A paint brush or mini roller will help with edges or small areas. If using a paint brush you can apply it straight from the tin. Work the liquid into the surface as evenly as you can. Apply more as necessary if you find you have very porous concrete and the coating is sinking in.

Don't apply too thickly or overload your brush or roller. If it drips Seal 'n' Tint will stain, which isn't serious, but means you will have to put another coat on to compensate.

Cover It

5 litres (1 gallon) of Seal 'n' Tint will cover approximately 37 square metres (400 square feet) with one coat. We recommend you apply a minimum of two coats, leaving 8 hours between coats. If your concrete is very absorbent you may need a third. The more coats you apply, the darker the final result will be.

Clean It

Remove as much of the product as possible before washing brushes, rollers and trays in water.

Don't Use It

Don't use Seal 'n' Tint on concrete that is less than 28 days old.

Dry It

You will be able to walk on it after approximately 16 hours, based on a minimum temperature of 15°C. The lower the temperature, the longer the drying time.

Seal 'n' Tint will be fully resistant to scuffing in 7 days at 15°C.

Store It

The shelf life of Seal 'n' Tint, if unopened, is one year. Do not allow to freeze.

Disposal and Safety information

Please see the Material Safety Data Sheet at www.paintpeople.co.uk for safety information.

Availability

Seal 'n' Tint is supplied in 5 litre containers.

Available from www.paintpeople.co.uk

Colour Range



Charcoal



Rustic
Brick

Due to Seal 'n' Tint's penetrative nature, it is advisable to carry out a test on a small area first to ensure you are happy with the colour and the finish. Free liquid samples are available on request.

While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.