

Highest Standards

With the **Dirt MedicTM** Hand operated adjusting wheel, control angle and cutting depth simultaneously.

Easy to use — Easily adjust cutting angle and depth without tools.

Fast — Quickly level infields and fill in low spots.

Tough — American Made using all welded steel construction and quality components.

Reliable — Backed by a 18-month warranty the Dirt $Medic^{TM}$ will give years of maintenance-free service.

Product Overview

The Dirt Medic™ Infield Drag & Groomer is specifically designed for use with garden tractors, light utility vehicles and ATV's to fill and level infields while still maintaining the durability of larger machines. The Dirt Medic™ has a wide 4 foot grooming path and the 5 foot brush kit will cover even the tire tracks left behind.

Features

- Towing wheels Two, 4 ply 12 inch diameter pneumatic tires on 410/350 x 6 wheels easily lower lift the unit for towing both on and off the field.
- Cutting path 48 inch wide, 0-2 inch adjustable for depth and cutting angle.
- Adjusting wheel Hand operated adjusting wheel controls and cutting depth simultaneously.
- Harrow bar our harrow bar has eight replaceable hardened steel 5/8" square spikes.
- Ballast Trays Two trays, each sized for standard cement blocks.
- Finishing Brush 5 foot brush leaves a professional smooth surface.

Chacifications

Specifications	
Item Name	Dirt Medic™
Item Number	10003315
Application	Baseball Infield Drag and Groomer
Material Type	All welded structural steel, industrial grade bearings with grease fittings
Equipment Requirements	Lawn tractor, ATV or utility vehicle with 500lbs towing capacity.
Shipping Dimensions	Pallet size 62" x 25" x 29"
Warranty	18 Months
Shipping weight	250 lbs.
Includes	Harrow bar, Scraper blade, Ballast trays, Finishing brush and Towing wheels.
TAA Compliance	Proudly made in the USA at our Aurora, Colorado facility



Reduce the cost of Infield Maintenance

With the Dirt Medic™





Product Features

Easy Towing: Two, 4 ply 12 inch diameter pneumatic tires on $410/350 \times 6$ wheels easily lower lift the unit for towing both on and off the field.



No Tools Required: Easily adjust cutting angle and depth without tools.



Harrow Bar: Our harrow bar has eight replaceable hardened steel 5/8" square spikes.



Ballast Trays: Two trays, each sized for standard cement blocks.

Finishing Brush: 5 foot brush leaves a professional smooth surface.