

DBK Drymatic II

Controlled Heat and Air Exchange System

Drymatic II is the latest innovation in water damage restoration from DBK Group. DBKs patented drying technology is truly unique in the world of restoration.

Drymatic II is smaller, lighter and even more powerful than its predecessor; giving technicians greater control over the drying process. Nothing increases the diffusion rate of bound water within a structure faster than the controlled application of heat.

Drymatic II works in harmony with Drymatic Boost and Wall & Floor Systems to deliver the most efficient drying system on the market.

TECHNICAL DATA

Voltage	120V 60Hz (230V available)
Power	1.4 kW
Maximum Current	11.6 A
Dimensions	37 x 25 x 14"
Weight	52 lb
Construction	Rotomolded
Max Airflow	380 cfm
Noise	56.4 dB
Recommended Drying Area	10,500 ft ³ (maximum)



Patent No.: US 9,015,960

- ### What's New:
- Tough Rotomolded Design
 - Touch-Screen User Interface
 - Stackable - Reducing Logistical Costs
 - Simplified Installation
 - Increased Airflow
 - Adaptive Heater Technology



Xactimate: WTRHTX

Contact us for more information!

Office: 864 599 1600

Email: sales@drymatic.com

Web: drymatic.com

Find us on Facebook and Twitter @DBKDrymatic