

## DBK Drymatic Wall & Floor System

**Targeted Heat Drying... At Its Finest**



The Wall & Floor System is designed to efficiently control the heated airflow created by the DBK Drymatic Boost Box.

The patented system uses micro-jets of warm, dry air to break the boundary layer of moisture at the surface of a water damaged material. The controlled heat generated by the DBK Boost Box is then driven into the structure, increasing the core temperature and increasing the diffusion rate of the bound water.

The Wall & Floor System, combined with the Boost Box, is the most effective target drying system on the market.

**Find us on Facebook and Twitter  
@DBKDrymatic**

### Mat Sizes available:

Available Sizes (L x W/H) approx.	Floor	Wall
	3' x 20" 3' x 3'	6.5' x 20" 6.5' x 3'
	6.5' x 20" 6.5' x 3' 6.5' x 5'	13' x 20" 13' x 3'
	10' x 20" 10' x 3' 10' x 5' 10' x 6.5'	

Fastening Method      High Strength Velcro

Joinable      Yes

Maximum Operating Temp      176°F

Washable      Warm, Soapy Water.  
Hand Wash Only

Additional mats and accessories available for special applications

### Features:

- Lightweight and Portable
- Reduces waste to landfill
- Requires no fixing to structure
- Wall mats are self-standing
- Reduces volume of air being managed, maximizing performance
- Washable and long-lasting
- Flame Retardant material



**Xactimate: WTRHTBL**

**Contact us for more information!**

**Office: 864 599 1600**

**Email: [sales-us@dbk-group.com](mailto:sales-us@dbk-group.com)**

**Web: [us.drymatic.com](http://us.drymatic.com)**

# Building Restoration