

**Typhoon 60**

**Features**

- High power to size ratio
- Lightweight
- Fixing - 35mm DIN-rail mount (EN50022)
- Built-in finger guard (flush fitting)



DBK's knowledge of thermal management gives us the experience to guide and support you with your technical challenges - we can manage the complete project from concept to full production release.

Typhoon 60		
Nominal Power Output at 10°C / 50°F	200W / 250W / 300W / 400W / 500W	
Nominal Input Voltage Heating Element	115V or 230V	
Nominal Input Voltage Fan	24V DC	
Max. Body Temperature (25°C / 77°F ambient)	74°C / 165°F	
Operating Temperature Range (°C / °F)	-20 to +70 / -4 to +158	
Storage Temperature Range (°C / °F)	-40 to +70 / -40 to +158	
Fan lifetime - L10/hrs at 30°C / 86°F (Std.)	74,000	
Fan Volumetric Flow (at zero static pressure) (m <sup>3</sup> /h / cfm)	30.5 / 18	
Dimensions	Cross Section (mm / ")	63 x 63.5 / 2.5 x 2.5
	Length (mm / ")	93 / 3.66
Weight (g / oz)	367 / 12.95	
Connection Type	Push In Terminal	
Ingress Protection (EN60529)	IP20	
Electrical Protection Class	SK II	
Recommended Fuse (Time Delay) 115/230V	4A / 4A / 6.3A / 6.3A / 8A	

Note: All data is for unit operated in vertical orientation.

