

# VT1512-IP

VERTICAL  
15 AMP  
IP POWER  
CONDITIONER

## PROFESSIONAL HOME THEATER

CUSTOM INSTALL POWER MANAGEMENT



### FEATURES

- Protect-or-Disconnect surge protection
- Standard EMI/RFI Filtration
- Over/Under voltage load disconnect
- Power Sequencing
- IP Monitoring and Control - BlueBOLT™ enabled for IP monitoring and control
- 12 individually controlled outlets, 3 spaced for wall warts, 6 turned 90°
- Ground lug to attach Panamax signal-line protection modules
- Steel chassis
- Sleek design ideal for vertical mounting to an equipment rack with included brackets
- 10 foot power cord with removable plug to customize length
- 15A Capacity with circuit breaker
- 3 year limited product warranty with \$5,000,000 Connected Equipment Protection Policy when used with Panamax signal-line protection modules.

### BlueBOLT™

BlueBOLT Provides Web-Based Remote Power Management to Monitor and Control Your System—From Anywhere, 24/7.

**PANAMAX**

[www.panamax.com](http://www.panamax.com)

# VT1512-IP

## Circuit Breaker:

Automatically trips when the load exceeds 15 amps. Push to reset.

## Rocker Power Switch:

When switched off, all outlets turn off immediately. When switched on, outlets turn back on in sequence.

## Network Connector:

Connect an Ethernet cable (not provided) between the NETWORK port and an Internet router or modem with an established Internet connection for remote control and monitoring.


## Network Reset Button:

Press using a paper clip, ball point pen, or other small object to reset connection to BlueBOLT™ cloud.

## Ground Lug:

Connect Panamax signal-line protection modules grounds to this terminal. Protecting data lines as well as AC lines from surges is required for the Connected Equipment Protection Policy warranty.

## Detailed View



Mounting Bracket Holes (4)



## LED Indicators

**POWER ON:** Illuminates when power is present to the device. Note: Check status indicators for individual outlets to determine if each outlet's power is on or off.

**UNSAFE VOLTAGE:** The Protection OK secondary indication is the status of the VT1512-IP's Over/Under voltage load disconnect feature. If the line voltage is less than 85 Vac or greater than 140 Vac the outlets will shut off and the Protection OK indicator will flash green. Power will automatically be restored when voltage returns to a safe level and the outlets will sequence to the original state prior to an over/under voltage load disconnect.

**PROTECTION OK:** Indicates status of the VT1512-IP's Protect-or-Disconnect surge protection feature. If the POWER LED is illuminated but the PROTECTION OK LED is off, contact Panamax technical support.

**BlueBOLT:** Indicates status of BlueBOLT connection.

**OFF:** Not connected to an active local area network (LAN)

**GREEN:** Connected to an active LAN, but cannot contact the BlueBOLT server/cloud

**BLUE:** Connected to an active LAN and is connected to the BlueBOLT server/cloud

**Outlets 1-3:** Spaced to accommodate large transformers (wall warts).

**Outlets 4-8:** Rotated 90° to accommodate large transformers (wall warts).


## Outlet Indicators

The VT-1512-IP features 12 outlets. With no BlueBOLT connection, the outlets will sequence on from 1-12, and turn off in the reverse sequence. When controlled via BlueBOLT, you have control of all 12 outlets individually

**LED lights indicate outlet status:**

**BLUE:** Indicates power status for an individual outlet

**OFF:** Indicates power is off for an individual outlet



# VT1512-IP SPECIFICATIONS

## AC Power

AC Power.....120Vac, 50/60Hz  
 Total Outlets.....12  
 Total Current Capacity.....15A (1800W)  
 Voltage Protection Rating  
 (UL 1449 4th Edition, 3,000A).....L-N500V, L-G500V, N-G500V  
 Protection Modes.....L-N, L-G, N-G  
 Initial Clamping Level.....200V Peak, 141 RMS  
 Energy Dissipation.....200 Joules  
 Peak Impulse Current.....12,000  
 Protect-or-Disconnect.....Yes  
 Thermal Fusing.....Yes  
 Cord Length.....Captive 10ft. cord  
 with removable NEMA 5-15P for length customization

## Environmental

Temperature.....0°C + 40°C (+32°F + 104°F)  
 Operating Humidity.....0 - 90% non-condensing  
 Over-voltage load disconnect.....140 Vac  
 Under-voltage load disconnect.....85 Vac  
 Filtration Technology Standard.....RFI/EMI Filtration  
 Filtration Rating.....18dB@100kHz, 53dB@1MHz, 18dB-53dB@100kHz-1MHz

Specifications subject to change due to product upgrades and improvements.

## PRODUCT MEASUREMENTS, WEIGHT AND UPC FOR ORDERING & SHIPPING

DIMENSIONS	WEIGHT	UPC
L 37" x W 1.75" x H 1.75"	5.85 lbs.	050616010344

MODEL: VT1512-IP



5919 Sea Otter Place, Suite 100, Carlsbad, CA 92010 • 800-472-5555  
 www.panamax.com • www.mybluebolt.com

## WARRANTIES\*

\$5,000,000 Connected Equipment Limited Lifetime Warranty • Limited 3 Year Product Warranty  
 \*Refer to actual warranty documentation for full details.