DATA



PRODUCT

E&H

770-3FRD

Tedlar Insulation Blanket Splicing Tape (Dull)

DESCRIPTION

A metalized tedlar insulation cover splicing tape.

AEROSPACE APPLICATION 770-3FRD is used in the fabrication of insulation blanket covers and for the installation of insulation blankets. It may be used for sealing sewn seams and for closing fabrication slits or holes around brackets, conduits or other objects that may exist after installation.

SPECIAL **FEATURES**

770-3FRD is flame retardant.

SPECIFICATIONS

FAR 25.853 (a,b)

BMS 5-149 Rev A Type 1 Class 3 Grade Form I

DMS 1984 Rev N Type 5 Class II

OFFSETS

Orcon OT-6

TECHNICAL DATA

Construction .0005 Mil Metalized Tedlar

20 x 10 Leno Polyester Scrim

.003 Mil Fire Retardant Acrylic

Pressure Sensitive Adhesive

PSTC-1 Peel Strenght:

On FR PRimed Aluminum

15 Min.

54.4 oz/inch Average

3 Day

129.6 oz/inch Average

30 Day

152.3 oz/inch Average

3.9 oz./square yard

Weight:

Flammability:

Burn Length

3.4 inches maximum

Flame Time

0 seconds

Drip Flame Time

No drips