

## PRODUCT DATA SHEET

# NST-20

## ANTI-SLIP / NON-SKID SAFETY TAPE

### DESCRIPTION:

NST-20, "Sure-Step" has an aggressive adhesive, which conforms to irregular surfaces. PVC surface is impregnated with silicone carbide (black) or aluminum oxide (colors) to provide a high traction, anti-slip, waterproof surface.

### APPLICATIONS:

For use indoors or outdoors; on walkways, ramps, and stairways; in machine shops, work areas, etc.; to comply with OSHA 1910.263(3).

### PHYSICAL PROPERTIES:

Tape Thickness	27.6 mil
Adhesive Thickness	2.4 mil
Carrier Base Film	3.93 mil PVC
Liner Type	White siliconized paper
Adhesive Type	Solvent Based Rubber
Adhesion to SST	49.3 oz/inch
Temperature Range	5°C to 50°C (41°F to 122°F)
General Grit Size	60 - 70
General Grit Type	Aluminum Oxide

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

10-02TWL

# Non-Skid Safety Tapes...

## PRODUCT NUMBER/SPECIFICATIONS

### **NST-20... "Sure-Step"**

32 mil. 60/80% Grit silicone oxide. High traction, anti-slip, water-proof, coated with an aggressive pressure-sensitive acrylic adhesive. For use indoors or outdoors; on walkways, ramps, stairways; in machine shops, work areas, etc.; to comply with OSHA 1910.263 (3). 3" core.

WIDTH	RLS/CS
<b>20 YD (60FT) BLACK</b>	
1" (25mm)	12
2" (50mm)	6
3" (75mm)	4
4" (101mm)	3
6" (152mm)	2
12" (305mm)	1
18" (457mm)	1
24" (609mm)	1
36" (925mm)	1

Alternative to 3M Safety Walk™.