

MASK-OFF COMPANY

STENCIL PAPERS PROTECTIVE PAPERS AND FILMS SPECIALTY COATINGS

P.O. BOX 1148 * 345 WEST MAPLE AVENUE * MONROVIA, CALIFORNIA 91016 * PHONE (626) 359-3261 FAX (626) 359-7160

PROTEX 20V

USES:

PROTEX 20V is a 20 mil latex saturated tape which has an external vinyl coating increasing its abrasion resistance. It is used in the protection of acrylic windows, canopies, windshields and certain metal and painted surfaces requiring increased protection. A liner allows product to be die-cut if desired. **PROTEX 20V** has proven to be excellent in protecting graphite composite surfaces and tooling from impact damage that may result in possible interlayer fracturing. This product is not intended for fly-away applications.

DO NOT USE ON COPPER, BRASS, OR ANODIZED ALUMINUM, OUTDOOR EXPOSURE IS NOT RECOMMENDED WITHOUT PRIOR TESTING.

TYPICAL PROPERTIES:

BACKING:

Basis wt., lbs./3,000 sq. ft. 175-187
Thickness, mils 19 - 23
Tensile strength, lbs./inch, M.D. 25 min.
Elongation, % M.D. 10 min.
Elmendorf Tear, grams, MD 280 min.
C.D. 360 min.

ADHESIVE:

Base Natural Latex Adhesion to steel, oz./in. width 30 - 40 (-5/+7)

(At time of manufacture) PSTC-1 (Modified)

LINER: Flat

STORAGE: Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.

STOCK ROLL SIZES:

36" X 30 YRDS 48" X 30 YRDS