



MASK-OFF COMPANY

STENCIL PAPERS

PROTECTIVE PAPERS AND FILMS

SPECIALTY COATINGS

P.O. BOX 1148 * 345 WEST MAPLE AVENUE * MONROVIA, CALIFORNIA 91016 * PHONE (626) 359-3261 FAX (626) 359-7160

PROTEX 412X

USES: **Protex 412X** is a self wound, 5 mil creped latex saturated paper, designed to protect anodized surfaces from abrasion or scratches during processing, such as forming, drilling, routing, etc. **PROTEX 412X** can remain on anodized surfaces for prolonged periods of time and still be removed without leaving any residue. This product is not intended for fly-away applications. **OUTDOOR EXPOSURE IS NOT RECOMMENDED.**

TYPICAL PROPERTIES:

BACKING:

Basis wt., lbs./3,000 sq. ft.	45-55
Thickness, mils	5.2-6.6
Tensile strength, lbs./inch, M.D.	18.7 min.
Elongation, % M.D.	9.3 min.
Elmendorf Tear, grams, C.D.	5.5 min.

ADHESIVE:

Base	Synthetic rubber/resin
Adhesion to steel, oz./in. width (At time of manufacture)	40 - 60 (-7/+10)
PSTC-1 (Modified)	

STORAGE: Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.

STOCK ROLL SIZES: (Available only in widths equal to 48")

48" X 60 YRDS