



MASK-OFF COMPANY

STENCIL PAPERS

PROTECTIVE PAPERS AND FILMS

SPECIALTY COATINGS

P.O. BOX 1148 * 345 WEST MAPLE AVENUE * MONROVIA, CALIFORNIA 91016 * PHONE (626) 359-3261 FAX (626) 359-7160

PROTEX 50

USES: **Protex 50** is a 4-5 mil latex saturated paper. It is used for protection of various metal and painted surfaces to reduce surface damage due to scratches. It can be left on the surface during fabrication and forming operations. The material is self-wound for ease in machine application to flat surfaces. Paper is printed in red "**SCRATCHES CAUSE REJECTIONS - HANDLE WITH CARE**" printed in red. This product is not intended for fly-away applications.

DO NOT USE ON COPPER, BRASS, OR ANODIZED ALUMINUM, OUTDOOR EXPOSURE IS NOT RECOMMENDED WITHOUT PRIOR TESTING.

TYPICAL PROPERTIES:

BACKING:

Basis wt., lbs./3,000 sq. ft.	42 - 49
Thickness, mils	4.1 - 5.1
Tensile strength, lbs./inch, M.D.	12.7 min.
Elongation, % M.D.	6.0 min.
Elmendorf Tear, grams, MD	56 min.
C.D.	56 min.

ADHESIVE:

Base	Natural Latex
Adhesion to steel, oz./in. width (At time of manufacture)	17 - 22 (-3/+4)
PSTC-1 (Modified)	

STORAGE: Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.

STOCK ROLL SIZES:

48" X 100 YRDS