



NOTE
 ▲ - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS
 OF .139 MAX DIA ON 1.000 ± .002 CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

| CHARACTERISTICS | ELECTRICAL DATA | SCALE FULL |
|-------------------------------------|---|---|
| OPERATING FORCE ----- 9-13 OZ | CONTACT ARRANGEMENT S P D T | DO NOT SCALE PRINT |
| RELEASE FORCE ----- 4 OZ MIN | -L96- 15 A-125, 250, OR 480 VAC 1/2 A-125 VDC; 1/4 A-250 VDC | UNLESS OTHERWISE NOTED |
| DIFFERENTIAL TRAVEL --- .0004-.0020 | -L288- -L306- -L315- | DIMENSIONS ARE IN INCHES |
| OVERTRAVEL ----- .219 MIN | 1/8 HP-125 VAC; 1/4 HP-250 VAC | TOLERANCES ARE: |
| | CE EN 05 EC 16A 250V ~ T85 5E4 | ONE PLACE (.0) ± .030 TWO PLACE (.00) ± .015 THREE PLACE (.000) ± .005 ANGLES ± .005 |
| | | WEIGHT .086 LB |

BZ-2RQ-A2
 PAGE 1 OF 1
M
 DRAWING NUMBER
 ISSUE 6
 REVISIONS
 A CO17410 O M W 22 FEB 65
 B 73287-D K D R 8 JULY 93
 C 77589 K D R 29 MAR 94
 D C093346 DLT 10 SEP 98
 E 0015139 TSG 23 AUG 05
 23 AUG 05
 14 MAY 05
 L S D
 65
 22 FEB 65
 O M W
 DRAWN
 FC-50376
 FORMTEK