

VD 4.8IP500

Indoor Production Screen

Specifications

Module Information

Pixel Pitch: 4.81 mm
Pixel Density: 43,264 Dots/m²
LED: SMD2020 3-in-1
Size (W * H * D): 500 * 250 * 14.5 mm
Resolution: 104 * 52

Cabinet Information

Size (W * H * D): 500 * 500 * 65 mm
Resolution: 104 * 104
Area: 0.25 m²
Weight: 6.5 Kg
Planeness: ≤ 1 mm
Materials: Die-cast Aluminium
Protection Rating: IP20
Life Span: 80,000 hr
Maintenance: LED Panel - Front / Rear Service,
Cabinet - Rear Service

Electrical Specification

PSU Input Voltage: 100 - 240V AC 50/60 Hz
Average Power Consumption: ≤ 220 W/m²
Max Power Consumption: ≤ 540 W/m²
Power Connection: Seetronic powerKON® In/Out

Optical Specification

Brightness(cd/m²): 800 - 1,200
Colour Temperature (K): 3,000 - 10,000 Adjustable
Horizontal Angle: 140°
Vertical Angel: 120°
Pixel Centre Offset: ≤ 3%
Brightness Uniformity: ≥ 97%
Chromaticity Uniformity: within +/- 0.003 Cx, Cy
Contrast Ratio: 3000:1

Image Process

Scan Mode: 1/13
Refresh Rate (Hz): ≥ 2,000
Data Connection: Seetronic etherKON®

Required Accessories

Video Controller
Hanging Beam
Angle Coupler for curved display (optional)
Road Case (optional)

