

VD 411

Indoor Installation Screen

Specifications

Module Information

Pixel Pitch: 4 mm
Pixel Density: 62,500 Dots/m²
LED: SMD2121 3-in-1
Size (W * H * D): 256 * 128 * 15 mm
Resolution: 64 * 32

Cabinet Information

Size (W * H * D): 768 * 768 * 135 mm *
Resolution: 192 * 192 *
Area: 0.59 m² *
Weight: 45 Kg/m² (Approx)
Planeness: ≤ 1 mm
Materials: Steel, Aluminium (Optional)
Protection Rating: IP20
Life Span: 50,000 hr
Maintenance: Rear Service,
Front Service (Optional)

Electrical Specification

Input Voltage: 100 - 240V AC 50/60 Hz
Average Power Consumption: ≤ 350 W/m²
Max Power Consumption: ≤ 580 W/m²

Optical Specification

Brightness(cd/m²): ≥ 1,200
Colour Temperature (K): 3,000 - 10,000 Adjustable
Horizontal Angle: 140°
Vertical Angel: 140°
Pixel Centre Offset: ≤ 3%
Brightness Uniformity: ≥ 97%
Chromaticity Uniformity: within +/- 0.003 Cx, Cy
Contrast Ratio: 2000:1

Image Process

Scan Mode: 1/16
Refresh Rate (Hz): ≥ 1,920

Required Accessories

Video Controller
Hanging Beam
Powercon In/Out (Optional)
Ethercon In/Out (Optional)

* Ratio of Module

