



COATABLE

AUTOPREP

SINGLE PLY PRIMER

Safety Data Sheet (02.02.22)

SECTION 1: Identification of the substance

1.1 PRODUCT IDENTIFIER: RUST BASE: GHS PRODUCT IDENTIFIER: Global Harmonized System #3208.90.0000

1.2 PRODUCT USE: Industrial solvent used as a primer over TPO/plastic roofing

1.3 COATABLE LLC: 916 W. Burbank Blvd, Unit C-279, Burbank CA 91506

1.4 EMERGENCY TELEPHONE NUMBER: 800-424-9300; 202/483-7616

SECTION 2: Hazard identification

2.1 Classification of the substance: This products is a flammable, solvent-based coating and should be treated according to all known safety precautions.

2.2 Label elements: Signal Word: WARNING

Hazard Symbol



Hazard Statement: Flammable liquid and vapor. Harmful in contact with skin. May cause cancer. Causes eye irritation. May cause respiratory irritation or damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

SECTION 3: Hazardous ingredients

HAZARDOUS INGREDIENTS	%	CAS/PIN
Solvent naphtha petroleum	80	64742-94-5
Modified chlorinated polypropylene with maleic anhydride	11.5	68609-36-9
Xylene	8.0	1330-20-7
Chloroform	0.5	67-66-3

SECTION 4: First aid measures

4.1 Description of first aid measures

INHALATION: Remove to fresh air. Give oxygen if required. Seek medical help.

EYES: Flush w/water for at least 15 minutes; rest eyes for 30 minutes and see physician if redness, burning or swelling persists.

SKIN: Remove contaminated clothing; wash affected areas w/mild soap & water.

INGESTION: Do not induce vomiting. Give 1-2 glasses milk or water. Seek medical attention according to amount of product ingested.



COATABLE

AUTOPREP

SINGLE PLY PRIMER

Safety Data Sheet (02.02.22)

SECTION 5: Firefighting measures

SPECIFIC HAZARDS: Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. The vapour is heavier than air, spreads along the ground and distant ignition is possible.

AUTOIGNITION TEMP.: 449-510C.

FLASH POINT & METHOD: 62-65.6C

FLAMMABLE LIMITS: 0.6-7%

SENSITIVITY TO STATIC DISCHARGE? NAV

MECHANICAL IMPACT? NAV

SPECIAL PROCEDURES: Firefighters should wear full-body protection & SCBA

MEANS OF EXTINCTION: Foam, water spray or fog. Dry chemical powder carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into the aquatic environment. Do not use water jet. Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental Release Measures

Use kitty litter or similar absorbent to contain spill. Transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Do not flush away residues with water; retain as contaminated waste. Use protective clothing; use non-sparking tools.

SECTION 7: Handling and Storage

STORAGE REQUIREMENTS: Storage temperature-ambient; keep away from flammables; avoid prolonged contact with natural, butyl or nitrile rubbers.

HANDLING PROCEDURES/EQUIPMENT: Ground all containers; use non-sparking tools and remove all ignition sources; avoid breathing vapors. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION 8: Exposure Controls and Personal Protection

PERSONAL PROTECTIVE EQUIPMENT: To be worn when spraying or within contained areas--Half-face respirator w/organic vapor filter, safety glasses w/shields, PVA or nitrile chemical-resistant gloves, skin protection; for all other applications, good judgement should be used.

ENGINEERING CONTROLS: To spray, mechanical exhaust ventilation is required

SECTION 9: Physical and Chemical Properties

PHYSICAL STATE:	Liquid
SOLUBILITY IN WATER:	Insoluble
APPEARANCE AND ODOR:	Colorless, aromatic odor
pH	NAV
DENSITY	Typical 893 kg/m3 @ 15C
BOILING POINT:	179-214C.
SPECIFIC GRAVITY:	0.88-0.91 @ 20C
ODOR THRESHOLD:	NAV
COEFF. WATER/OIL:	NAV
EVAPORATION RATE:	<1.0
VOLATILES:	80%
VAPOUR PRESSURE:	<1.3 kPa @ 20C/68F



COATABLE

AUTOPREP

SINGLE PLY PRIMER

Q_crwB_r_ Qf ccr & 0., 0,00'

QCARQML / . 8Qr` jgw_l b Pc_arg gw

AFCK Q? J G AMKN? RCQ QRB Strong oxidizing agents

AML B QML Q MD G QR? @G QRB Stable under normal conditions of use; avoid heat, sparks, open flames & other ignition sources

F? X? PBMSQ BCAMK NMQ QML NPMB SARQ Thermal decomposition is highly dependent on conditions; a complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

QCARQML // 8 Rm/ganjmw G dtpk _rgri

? ASRC MP? J RMV Q RB Low toxicity; aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal

? ASRC BCPK? J RMV Q RB Low toxicity

? ASRC G F? J? RML RMV Q RB Low toxicity; high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea

A? PA G ME CL Q RB Limited evidence--naphthalene

Q G Q P GR? RML 8 Slight

PCNP MB SARQ C 8 Causes foetotoxicity in animals

CVC Q P GR? RML 8 Moderately irritating to eyes (but insufficient to classify)

PCQNG? RMP W Q P GR? RML 8 Inhalation of vapours or mists may cause irritation to the respiratory system; insufficient to classify

QCL Q GR? RML 8 Not a skin sensitiser

QCARQML / 08 Canjme g_j G dtpk _rgri

? g 8.36 lbs./gallon

U _rc p 8 Floats on water; expected to be readily biodegradable

Qmg 8 Absorbs to soil and has low mobility

QCARQML / 18 B g n n q_j Anl q d p c p _rgri

Dispose of as paint/aluminum waste according to local regulations.

QCARQML / 28 Rp_l q n m r G dtpk _rgri

Listed materials under Superfund Amendments & Reauthorization Act of 1988 (SARA) 311, 312, 313

NPCN? PCB @ MB Coatable, LLC

B? RC 5/12/15