

ELLISON STUDIOS.

Fabric Specification Guide

The ELLISON STUDIOS. fabric specifications and care instructions guide. The following is a detailed summary of all the upholstery fabrics used in ELLISON STUDIOS. and is to be used for informational purposes only and any additional care information can be found in the Product Care Guide.

Contact Us

For more information or if you have any additional questions, please contact us at info@ellisonstudios.com or visit our website www.ellisonstudios.com



Fabric Specifications Guide

Collection	Avalon	Bronte	Byron
Colour(s)	Piccolo Fawn (USA only)	La Crème, Whipped Cream	Biscuit, Oyster, Wheat Dove (USA only)
Fabric Type	Velvet Domestic	Woven Boucle Knit Domestic	Slub Plain Weave Domestic
Composition	100% Polyester	81% Polyester 19% Acrylic	30% Linen 20% Viscose 50% Polyester
Weight (gsm)	480gsm	630gsm	520gsm
Origin	China	China	China
Cleaning Code	S	S	W
Care Icons			
Testing Results			
Abrasion Testing	Exceed 50,000 ISO 12947-2:2016;	Exceed 50,000 ISO 12947-2:2016;	Exceed 40,000 ISO 12947-2:2016
Colour Fastness to Rubbing	Dry 4-5 Wet 4-5 ISO 105-X12:2016	Dry 4-5 Wet 4 ISO 105-X12:2016	Dry 4-5 Wet 4-5 AATCC TM8-2016e
Colour Fastness to Light	4 ISO 105-B02 ; 2014	4-5 ISO 105-B02:2014;	3-5 AATCC 16.3-20
Pilling Resistance	4-5 ISO 12945-2:2000;	4 ISO 12945-2:2000;	3-5 D3514/D3514M-16 (2020)

Collection	Cabarita	Collaroy (Outdoor)	Hamptons
Colour(s)	Hazel, Natural	Static	Oat
Fabric Type	Brushed Plain Weave Domestic	Plain Woven Fabric Domestic	Brushed Cotton Canvas
Composition	100% Hemp	60% Olefin 40% Polyester	100% Cotton
Weight (gsm)	465gsm	330gsm	490gsm
Origin	China	China	China
Cleaning Code	S	SW	S
Care Icons			
Testing Results			
Abrasion Testing	Exceed 15,000 ASTM D4157-13 (2022)	Exceed 30,000 ASTM D4966-12(2016)	Exceed 15,000 ASTM D3512 (2022)
Colour Fastness to Rubbing	Dry 4 Wet 3 AATCC 116-18	Dry 5 Wet 5 AATCC TM8-2016e	Dry 5 Wet 5 AATCC 116-18
Colour Fastness to Light	2 AATCC 16.2 - 2020	4.5 AATCC TM 16.3-2020	2.5 AATCC 16.3-2020
Pilling Resistance	4 ASTM D3514M- 6R2020	4 ASTM D3512M-16	4.5 ASTM D3514M- 6R2020

Collection	Hyams	Malibu	Montauk
Colour(s)	Sable	Caramel, Dune Agave (USA only)	Off-White
Fabric Type	Textured Woven Fabric Domestic	Woven Tufted Velvet Domestic	Faux Shearling Domestic
Composition	12% Wool 52% Acrylic, 5% Linen, 31% Polyester	100% Polyester	100% Polyester
Weight (gsm)	800gsm	460gsm	520gsm
Origin	China	China	China
Cleaning Code	SW	SW	X
Care Icons	☞ ☒ ☒ ☒ ☒	☞ ☒ ☒ ☒	☞ ☒ ☒ ☒
Testing Results			
Abrasion Testing	Exceed 15,000 ASTM D4966-22	Exceed 30,000 ASTM D4966-12(2016)	Exceed 40,000 ISO 12947-2:2016
Colour Fastness to Rubbing	Dry 5 Wet 4.5 AATCC 116-18	Dry 4-5 Wet 4-5 AATCC TM8-2016e	Dry 4-5 Wet 4-5 ISO 105X12:2016
Colour Fastness to Light	4.5 AATCC TM 16.3-2020	3 AATCC 16.3-2014	4-5 AATCC 16.3-20
Pilling Resistance	4 ASTM D3512-22	4 ASTM D3512/D3512M-16	4 ISO 12945-2:2000

Collection	Paddington	Palermo (Outdoor)	Sandon
Colour(s)	Cashew	Sand	Burnt Butter, Crumpet
Fabric Type	Woven Knit	Woven Fabric	Woven Velvet Fabric
Composition	100% Polyester	100% Polyester	100% Recycled Polyester
Weight (gsm)	433gsm	240gsm	490gsm
Origin	China	China	China
Cleaning Code	X	SW	X
Care Icons	☞ ☒ ☒ ☒ ☒	☞ ☒ ☒ ☒	☞ ☒ ☒ ☒
Testing Results			
Abrasion Testing	Exceeds 15,000 ASTM D4966-22	Exceed 30,000 ASTM D4966-12(2016)	Exceed 50,000 ISO 12947-2:2016;
Colour Fastness to Rubbing	Dry 5 Wet 5 AATCC 116-18	Dry 5 Wet 5 AATCC TM8-2016e	Dry 4-5 Wet 4-5 ISO 105-X12:2016
Colour Fastness to Light	4.5 AATCC TM 16.3-2020	4.5 AATCC TM 16.3-2020	5 ISO 105-BO2 ; 2014
Pilling Resistance	3 ASTM D3514-16 (2020)	4 ASTM D3512M-16	4-5 ISO 12945-2:2000;

Collection	Shearling	Sorrento	
Colour(s)	Natural	Moon	
Fabric Type	Shearling Wool	Velvet Corduroy Domestic	
Composition	100% Leather	100% Polyester	
Weight (gsm)	N/A	391gsm	
Origin	Australia / China	China	
Cleaning Code	X	W	
Care Icons			
Testing Results			
Abrasion Testing	N/A	Exceed 15,000 ISO 12947-2:2016	
Colour Fastness to Rubbing	Dry 4 Wet 4 ISO 11640-2012	Dry 4-5 Wet 4-5 ISO 105X12:2016	
Colour Fastness to Light	3 ISO 105-BO2 ; 2014	4 AATCC 16.3-20	
Pilling Resistance	N/A	4-5 ISO 12945-2:2000	

Standard Cleaning Codes

Industry standard cleaning codes indicate the correct cleaning method based on the type of fabric.

O: Spot clean in cold water using biodegradable detergent or eco-friendly soap; air dry. Organic dry cleaning is also recommended.

W: Spot clean using distilled water and water-based cleaning agents or foam only.

S: Spot clean with mild, water-free cleaning solvents only. Do not use water or dry clean.

SW: Spot clean using distilled water and water-based cleaning agents, foam or mild water-free cleaning solvents.

X: Vacuum or lightly brush to remove overall soil. Never use water, foam or liquid cleaning agents.

Note: For prewashed fabrics upholstered onto the frame, follow the S cleaning code.

Upholstery Care

Rotate cushions and pillows weekly to distribute wear. Vacuum upholstery weekly using the upholstery attachment and crevice tool of your vacuum to remove loose particles.

Periodic cleaning by a professional upholstery cleaning service is the only recommended cleaning method for your upholstery, annual cleaning is suggested, but this may vary depending on use.

To prevent possible "bleeding" of ink onto fabric, do not leave newspapers or other printed materials lying on upholstery.

Take special care when spraying household chemicals and commercial products near upholstery.

Avoid placing your furniture in direct sunlight. All fabric and leather will fade over time. Applying non-commercial scented fabric fresheners, neutralizers and fabric protectors is never recommended.

Spills and Spot Cleaning

In some cases, spot cleaning can cause a ring or fading. It is best to have the entire piece or cushion casing cleaned by a professional upholstery cleaner to ensure uniform results. If you decide to spot clean on your own, check the standard cleaning code to determine the correct type of product to use. Always blot never rub spills immediately with a clean, absorbent white cloth. Blot from the outside to the middle of the affected area to prevent rings.

Pile fabrics may require brushing with a nonmetallic, stiff bristle brush to restore appearance. Always pretest cleaning agents in a small inconspicuous area. Never use strong chemicals or detergents.

ELLISON STUDIOS.