



GENERAL INFORMATION

At last a fisheye additive that does not need to be used in every coat. Use KE170 to correct fisheye or crater defects. Works with lacquer, urethane, polyurethane, acrylic urethane, acrylic enamel, etc. A must have product for your paint shop.



MIXING RATIO

Clear

Add 0.1 Oz (2.5 grams) Krator Eliminator per mixed quart.

HEALTH AND SAFETY

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

IMPORTANT: The contents of this package have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

Use component as instructed per Valspar guidelines. Verify that intended end use of component is in compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

WWW.HOUSEOFKOLOR.COM

valspar