

acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/26/2017 Version number 4 Reviewed on 10/26/2017

1 Identification

Trade name: RF741 Rework Flux

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation: Soldering flux

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Kester Inc. 800 West Thorndale Avenue Itasca, IL 60143 USA Tel (630) 616-4000 Tel International 00 1 630 616-4000

ITW Specialty Materials (Suzhou) Co., Ltd. Heng Qiao Road Wujiang Economic Development Zone Suzhou, Jiangsu 215200 China Tel +86 512 82060808

Kester GmbH Ganghofer Strasse 45 D-82216 Gernlinden Germany Tel +49 (0) 8142 4785 0

Information department: Product Compliance: EHS_Kester@kester.com

Emergency telephone number:

CHEMTREC 24-Hour Emergency Response Telephone Number: (800) 424-9300

CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number: (703) 527-3887

2 Hazard(s) identification

Classification of the substance or mixture



Health hazard

Repr. 1 H360 May damage fertility or the unborn child.



Skin Sens. 1 H317 May cause an allergic skin reaction.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms





GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

Halogenated organic diol

(Contd. on page 2)



acc. to OSHA HCS 29CFR1910.1200

Version number 4 Reviewed on 10/26/2017 Printing Date 10/26/2017

Trade name: RF741 Rework Flux

(Contd. of page 1)

Hazard statements

H317 May cause an allergic skin reaction. H360 May damage fertility or the unborn child.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system: NFPA ratings (scale 0 - 4)



Health = 0Fire = 1Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *0Fire = 1Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Description: Mixture of the substances listed below with nonhazardous additions.

CAS No.	Description		% Range
CAS: 872-50-4	N-methyl-2-pyrrolidon	е	1-3%
	Repr. 1B, H360 Skin Irrit. 2, H315; Flam. Liq. 4, H227	Eye Irrit. 2A, H319; STOT SE 3, H335	
Trade Secret	Halogenated organic		0.1- 1%
	Acute Tox. 4, H302	2; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	

4 First-aid measures

Description of first aid measures

General information: Follow general first aid procedures.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly. After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Seek immediate medical advice.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/26/2017 Version number 4 Reviewed on 10/26/2017

Trade name: RF741 Rework Flux

(Contd. of page 2)

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

Nitrogen oxides (NOx)

In case of fire, the following can be released:

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Environmental precautions: Do not allow to enter sewers/ surface or ground water. **Methods and material for containment and cleaning up:** Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:	
CAS: 872-50-4 N-methyl-2-pyrrolidone	30 ppm
Dicarboxylic Acids	20 mg/m ³
PAC-2:	
CAS: 872-50-4 N-methyl-2-pyrrolidone	32 ppm
Dicarboxylic Acids	230 mg/m ³
PAC-3:	
CAS: 872-50-4 N-methyl-2-pyrrolidone	190 ppm
Dicarboxylic Acids	590 mg/m ³

7 Handling and storage

Handling:

Precautions for safe handling Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/26/2017 Version number 4 Reviewed on 10/26/2017

Trade name: RF741 Rework Flux

(Contd. of page 3)

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits.

CAS: 872-50-4 N-methyl-2-pyrrolidone

WEEL Long-term value: 10 ppm

Skin

Additional information:

PEL = Permissible Exposure Limit (OSHA)

TLV= Threshold Limit Value (ACGIH)

OSHA= Occupational Safety and Health Administration

ACGIH= American Conference of Governmental Industrial Hygienists

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Breathing equipment:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:



Protective gloves

Material of gloves:

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Paste

Color: Amber colored

Odor: Mild

pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined.

(Contd. on page 5)



acc. to OSHA HCS 29CFR1910.1200

Version number 4 Reviewed on 10/26/2017 Printing Date 10/26/2017

Trade name: RF741 Rework Flux

(Contd. of page 4)

Boiling point/Boiling range: 204 °C (399.2 °F)

95 °C (203 °F) Flash point:

Ignition temperature: 186 °C (366.8 °F)

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density at 20 °C (68 °F): 1 g/cm³ (8.35 lbs/gal)

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Solvent content:

32.6 % Organic solvents: Solids content: 57.7 %

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: Strong acids, strong oxidizers.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute to	oxicity	/ -			
LD/LC50 values that are relevant for classification:					
CAS: 55934-93-5 [(butoxymethylethoxy)methylethoxy]propan-1-ol					
Oral	LD50	2,800 mg/kg (rat)			
CAS: 872-50-4 N-methyl-2-pyrrolidone					
		3,914 mg/kg (rat)			
Dermal	LD50	8,000 mg/kg (rabbit)			

Primary irritant effect:

on the skin: No irritant effect. on the eye: Irritating effect.

Sensitization:

Sensitization possible through inhalation. Sensitization possible through skin contact. Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories

CAS: 102-71-6 2,2',2"-nitrilotriethanol

(Contd. on page 6)

3



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/26/2017 Version number 4 Reviewed on 10/26/2017

Trade name: RF741 Rework Flux

(Contd. of page 5)

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

13 Disposal considerations

Waste treatment methods

Recommendation:

Disposal must be made according to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number

DOT, ADR, ADN, IMDG, IATA Not applicable

UN proper shipping name
DOT, ADR, ADN
Not applicable

IMDG, IATA

Not applicable

Not regulated

Transport hazard class(es)

DOT, ADR, ADN, IMDG, IATA

Class Not applicable

Packing group

DOT, IMDG, IATA Not applicable

Marine pollutant: No

Special precautions for user Not applicable.

Transport in bulk according to Annex II of MARPOL73/78

and the IBC CodeNot applicable.UN "Model Regulation":Not applicable

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

All ingredients are listed on the following Government Inventories:

China: Inventory of Existing Chemical Substances in China (IECSC)

Korea: Korea Existing Chemicals List (ECL)

(Contd. on page 7)



acc. to OSHA HCS 29CFR1910.1200

Reviewed on 10/26/2017 Printing Date 10/26/2017 Version number 4

Trade name: RF741 Rework Flux

(Contd. of page 6)

European Inventory of Existing Commercial Chemical Substances (EINECS) Inventory of Existing and New Chemical Substances (ENCS) Europe:

Japan:

Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)

USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

USA The following information relates to product regulation specific to the USA.

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

CAS: 872-50-4 N-methyl-2-pyrrolidone

TSCA new (21st Century Act) (Substances not listed)

Halogenated organic diol

California Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity:

N-methyl-2-pyrrolidone

Carcinogenic categories

EPA (Environmental Protection Agency)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

CANADA:

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the Safety Data Sheet (SDS) contains all of the information required by the CPR.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms





GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

Halogenated organic diol

Hazard statements

H317 May cause an allergic skin reaction. H360 May damage fertility or the unborn child.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P405 Store locked up.

(Contd. on page 8)



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/26/2017 Version number 4 Reviewed on 10/26/2017

Trade name: RF741 Rework Flux

(Contd. of page 7)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

CAS: 872-50-4 N-methyl-2-pyrrolidone

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibilty as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing Safety Data Sheet (SDS): Product Compliance / EHS Department

Contact: EHS_Kester@kester.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le tránsport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of

Dangerous Goods by Road)

IMDĞ: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 1: Reproductive toxicity - Category 1

Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.