



SPECIFICATIONS:

- POWER: 280 12W, 430 24W
- VOLTAGE 24V
- LUMEN EFFICIENCY: 61 LM/W
- CRI >80
- IP RATING : 1P67
- BEAM ANGLE 110DEGREE
- COLOR TEMP 6000-6500K
- LIFETIME; 50,000 HOURS
- WORKING TEMP -20-45C
- INSTALATION TYPE : RECESS MOUNTING

MODEL#	MWL-Q280-L	MWL-Q430-L
L1	280	430
L2	133	208
L3	250	400
L4	252	402

DEFAULTS		STACK-LIGHT.COM	
ANSI THIRD ANGLE	COUNTERSINKS: .5	TITLE	--
UNITS ARE IN mm X.X +/- .5 X.XX +/- .1 WHEN INCHES ARE USED X.X +/- .03 X.XX +/- .010 X.XXX +/- .005		MATERIAL	
DESIGNED DATE 7/15/2022		VENDOR	
LAST SAVED DATE 10/10/2022		VENDOR#	
DRAWING NO.		REV	
DRAWG SIZE: B		MWL-Q-280	
BREAK ALL SHARP EDGES		WEIGHT 0.856 LBS	
PROPRIETARY AND CONFIDENTIAL			
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF STACK-LIGHT.COM. ANY REPRODUCTION WITHOUT THE WRITTEN PERMISSION OF STACK-LIGHT.COM. IS PROHIBITED.			