



PART#	MAX SENSING DISTANCE	SPOT DIAMETER	SENSOR TYPE	SENSING TARGET
PS-MTB-30M	30 METER	4.5mm SPOT @ 30mm, 5mm @ 50mm, 6.5mm @ 100mm	THROUGH BEAM	TRANSMITER / RECEIVER
PS-MTB-15M	15 METER	4.5mm SPOT @ 30mm, 5mm @ 50mm, 6.5mm @ 100mm	THROUGH BEAM	TRANSMITER / RECEIVER
PS-MTB-10M	10 METER	4.5mm SPOT @ 30mm, 5mm @ 50mm, 6.5mm @ 100mm	THROUGH BEAM	TRANSMITER / RECEIVER
PS-MR-3M	3 M	4.5mm SPOT @ 30mm, 5mm @ 50mm, 6.5mm @ 100mm	RETROREFLECTIVE	REFLECTOR OR REFLECTIVE TAPE
PS-MD-150	150mm	4.5mm SPOT @ 30mm, 5mm @ 50mm, 6.5mm @ 100mm	DIFFUSE	READS FROM OBJECT BEING SENSED
PS-LTB-15M	15M		THROUGH BEAM	TRANSMITER / RECEIVER
PS-LTB-10M	10M		THROUGH BEAM	TRANSMITER / RECEIVER
PS-LTB-7M	7M		THROUGH BEAM	TRANSMITER / RECEIVER
PS-LR-3M	3M		RETROREFLECTIVE	REFLECTOR OR REFLECTIVE TAPE
PS-LR-300	300mm		DIFFUSE	READS FROM OBJECT BEING SENSED
PS-LD-100	100mm		DIFFUSE	READS FROM OBJECT BEING SENSED

DEFAULTS		STACK-LIGHT.COM	
ANSI THIRD ANGLE	COUNTERSINKS	TITLE	---
		MATERIAL	
UNITS ARE IN mm X.X +/- .5 X.XX +/- .1 WHEN INCHES ARE USED X.X +/- .03 X.XX +/- .010 X.XXX +/- .005	DESIGNED DATE	1/12/2024	DRAWING NO.
BREAK ALL SHARP EDGES	LAST SAVED DATE	1/30/2024	REV
	DWG SIZE:	B	PS-PHOTO SENSOR
			WEIGHT: 0.027 LBS
<b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF STACK-LIGHT.COM. ANY REPRODUCTION WITHOUT THE WRITTEN PERMISSION OF STACK-LIGHT.COM, IS PROHIBITED.			