

### RAFFLES PAINT R.AQUA GLOSS 2 IN 1

- Description** : RAFFLES PAINT R.AQUA GLOSS 2 IN 1 is a high gloss water based acrylic paint which performs as both top coat and primer, 2 coats to replace traditional 1 primer/2 top coats painting system.  
It is a low odour, low VOC and environmentally friendly paint.
- Type** : Acrylic emulsion
- Finish** : High gloss
- Recommended Uses** : Suitable for painting of wood, metal and cementitious surfaces.  
It has good resistant to wood tannin and good anti-corrosion properties if painted on metal such as steel, galvanized steel and aluminium surfaces.
- Features** :
- Excellent hiding power and durability
  - High gloss
  - Excellent tannin resistance, anti-corrosion and water resistance
  - Low odour and low VOC (Volatile Organic Compound)
  - No Alkyl Phenol Ethoxylate (APE) surfactant, formaldehyde and ammonia are used
  - Non-toxic, does not contain lead, mercury and heavy metals
  - Environmentally friendly

### APPLICATION DATA

- Method** : Roller, brush or spray
- Theoretical Coverage** : 12-14 m<sup>2</sup> / litre
- Dilution** : No dilution is necessary for best performance
- Surface Preparation** : Ensure surface is clean, dry and stable. Loose film, rust, oil, fungus and other foreign matters should be removed from the surfaces before painting.

## **RAFFLES PAINT R.AQUA GLOSS 2 IN 1**

<b>Drying Time at 30°C</b>	:	Surface Dry - 30 minutes Hard Dry - 2 hours
<b>Over coating Time</b>	:	2 hours under normal conditions
<b>Recommended painting system</b>	:	2 coats of R.AQUA GLOSS 2 IN 1
<b>Cleaning</b>	:	All equipment should be cleaned with water immediately after use
<b>Disposal</b>	:	Dispose off waste paints and containers according to local environmental regulations.

### **GENERAL INFORMATION**

<b>Solid Content</b>	:	50 ± 2% by weight (based on white colour)
<b>Specific Gravity</b>	:	1.23 ± 2% kg / litre (based on white colour)
<b>Packing</b>	:	1 and 5 litres
<b>Storage</b>	:	Store in a tightly sealed container in a cool and dry place
<b>Shelf Life</b>	:	Up to 2 years in a tightly sealed container
<b>Precaution</b>	:	Avoid direct contact with sensitive skin. Use appropriate personal protective equipment. Ensure good ventilation during application.

### **RAFFLES PAINT PTE LTD**

**1 Tuas South Avenue 6 #04-04 Singapore 637021**

[hello@rafflespaint.com](mailto:hello@rafflespaint.com)

[www.rafflespaint.com](http://www.rafflespaint.com)

**Disclaimer:** The information provided above is intended to give a description of the product's performance under specific use conditions. Nevertheless, we cannot assume any responsibility for its use since circumstances under which the products are applied is subjected to many variations. We reserve the right to alter the given data without notice.