



SORAA LED MR16 LAMPS- INTERNATIONAL

Product Family	Reference Number	Product Code	Beam	Field	Luminous Intensity	Watts	Lumens	Lm/W	90° Lumens	SNAP SYSTEM
VIVID 2700K 9W	SM16-09-25D-927-03-S3	01221	25	40	2570	9	465	52	435	-
CRI 95, R9 95	SM16-09-36D-927-03-S3	01229	36	57	1210	9	465	52	435	-
VIVID 3000K 9W	SM16-09-25D-930-03-S3	01225	25	40	2700	9	490	54	470	-
CRI 95, R9 95	SM16-09-36D-930-03-S3	01233	36	57	1280	9	490	54	470	-
VIVID 2700K 7.5W	SM16-07-10D-927-03-S3	01185	10	20	5710	7.5	390	52	350	Yes
CRI 95, R9 95	SM16-07-25D-927-03-S3	01197	25	40	2260	7.5	410	55	380	-
	SM16-07-36D-927-03-S3	01209	36	57	1070	7.5	410	55	380	-
VIVID 3000K 7.5W	SM16-07-10D-930-03-S3	01189	10	20	6000	7.5	410	55	380	Yes
CRI 95, R9 95	SM16-07-25D-930-03-S3	01201	25	40	2400	7.5	435	58	415	-
	SM16-07-36D-930-03-S3	01213	36	57	1130	7.5	435	58	415	-
VIVID 4000K 7.5W	SM16-07-10D-940-03-S3	01191	10	20	6290	7.5	430	57	395	Yes
CRI 95, R9 95	SM16-07-25D-940-03-S3	01203	25	40	2510	7.5	455	61	435	-
	SM16-07-36D-940-03-S3	01215	36	57	1190	7.5	455	61	435	-
VIVID 5000K 7.5W	SM16-07-10D-950-03-S3	01193	10	20	6290	7.5	430	57	395	Yes
CRI 95, R9 95	SM16-07-25D-950-03-S3	01205	25	40	2510	7.5	455	61	435	-
	SM16-07-36D-950-03-S3	01217	36	57	1190	7.5	455	61	435	-
VIVID 2700K 6W	SM16-06-25D-927-03-S3	01237	25	40	1600	6	290	48	265	-
CRI 95, R9 95	SM16-06-36D-927-03-S3	01249	36	57	750	6	290	48	265	-
VIVID 3000K 6W	SM16-06-25D-930-03-S3	01241	25	40	1710	6	310	52	285	-
CRI 95, R9 95	SM16-06-36D-930-03-S3	01253	36	57	810	6	310	52	285	-
BRILLIANT 2700K 9W	SM16-09-25D-827-03-S3	01219	25	40	3090	9	560	62	525	-
CRI 80, R9 > 0	SM16-09-36D-827-03-S3	01227	36	57	1460	9	560	62	525	-
BRILLIANT 3000K 9W	SM16-09-25D-830-03-S3	01223	25	40	3260	9	590	66	565	-
CRI 80, R9 > 0	SM16-09-36D-830-03-S3	01231	36	57	1540	9	590	66	565	-
BRILLIANT 2700K 7.5W	SM16-07-10D-827-03-S3	01183	10	20	6950	7.5	475	63	430	Yes
CRI 80, R9 > 0	SM16-07-25D-827-03-S3	01195	25	40	2760	7.5	500	67	465	-
	SM16-07-36D-827-03-S3	01207	36	57	1310	7.5	500	67	465	-
BRILLIANT 3000K 7.5W	SM16-07-10D-830-03-S3	01187	10	20	7320	7.5	500	67	465	Yes
CRI 80, R9 > 0	SM16-07-25D-830-03-S3	01199	25	40	2900	7.5	525	70	500	-
	SM16-07-36D-830-03-S3	01211	36	57	1370	7.5	525	70	500	-
BRILLIANT 2700K 6W	SM16-06-25D-827-03-S3	01235	25	40	1960	6	355	59	325	-
CRI 80, R9 > 0	SM16-06-36D-827-03-S3	01247	36	57	930	6	355	59	325	-
BRILLIANT 2700K 6W	SM16-06-25D-830-03-S3	01239	25	40	2070	6	375	63	345	-
CRI 80, R9 > 0	SM16-06-36D-830-03-S3	01251	36	57	980	6	375	63	345	-

Specifications are for lamps at stable operating conditions in well ventilated fixtures (25°C ambient)

*Energy Star minimum