



it's cool to be safe
explosion proof solution for the global market

Supermec

explosion proof electrical equipment





GUA

CSD

GUB - A

GUBA - A

GUBA - S

EJB - A

EJB - S

ECS

UH - UP

CSE - A

CSE - P

CSE - S

WH - WP - WA

UVB - UVD

it's cool to be safe
explosion proof electrical equipment



WH - WP- WA

The WH - WP operators and WA instruments are normally used in the chemical and petrochemical plants, off-shore platforms, refineries and any other industry where hazardous atmospheres (gas and combustible dust) are potentially present.

The WH - WP - WA range has been designed to meet the main requirements of power distribution, monitoring and signaling, and other electrical functions inside the hazardous area of the plant.



Function

The WH - WP - WA series are normally installed on CSE enclosures series used for the following main applications:

- control station and instrument housing
- instrument housing
- motor starter unit
- lighting control panel


and fitted with other electrical and/or electronic equipment as per our client specific requirements.

Construction

The material used to manufacture the UH-UP operators and WA instruments have been studied to grant the maximum protection against the highly corrosive agents present in these industries:

- the external components (handle, push-button, diffuser, ect.) are made of high-quality antistatic and UV-protected polymers and provided with EPDM sealing to maintain the IP66 level of protection of whole control station;
- the internal Ex d components are made of high quality thermoplastic and are available for standard installation on cover or, as option, on a dedicated mounting rail;
- the larger handles are padlockable in different positions (upon request)
- the LED units for pilot light and luminaire push button are available with two range of voltage as indicated in the ordering table;
- the rated current of Ex switch module is up to 16 Amp. and its mechanical life is 1,000,000 times;
- the high brightness and the electrical life of LED units are granted for a minimum of 100,000 hours;
- the diffuser of pilot lights and luminaire push button units have a special design to grant a high visibility degree in any situation
- the external components are fixed directly on cover with a Ø 30 mm. hubs and a directional anchor point depending by type of installation requested.

The installation of Ex operators and instruments inside the enclosures can be done according to the limits of certification in terms of distance and heat dissipation. Any configuration based on client requirements must be performed by Supermec.



Protection

certificate number:	IECEX CML 17.0088U	CML 17 ATEX 1173U	TC RU C-IT.AA87.B.00509
	IECEX CML 17.0089U	CML 17 ATEX 1174U	
marking:	II 2GD Ex db eb IIC T6 Gb Ex tb IIIC T85°C Db		
ambient temperature:	-55°C +60°C		
degree of protection:	IP66		
conformity:	Directive ATEX 2014/34/EU		TP TC 012/2011
standards:	IEC-EN60079-0	IEC-EN60079-1	IEC-EN60079-7
	ГОСТ 31610.0	ГОСТ IEC 60079-1	ГОСТ P МЭК 60079-7
	IEC-EN60079-11	IEC-EN 60079-26	IEC-EN60079-31
	ГОСТ 31610.11	ГОСТ P МЭК 60079-26	ГОСТ P МЭК 60079-31
category:	suitable for Zone 1- 2 (gas) and Zone 21 - 22 (dust)		



WPBS - WPBH - WPBHP

Handle unit for rotary switch up to 16 Amp. complete with integrated label with different indications as per different schemes listed.

WPBHP model is provided with a padlockable system in OFF position, to increase the level of security by unauthorized operations. The handle can be equipped with two padlocks.



2 poles 16 A switches

WPBS



WPBH - WPBHP



Code	Padlock	Label	Contact schematic for operating position
WPBS 1		0 I	
WPBH 1		0 I	
WPBHP 1	•	0 I	
WPBS 2		I II	
WPBH 2		I II	
WPBHP 2	•	I II	
WPBS 3		0 I II	
WPBH 3		0 I II	
WPBHP 3	•	0 I II	
WPBS 4		0 I II	
WPBH 4		0 I II	
WPBHP 4	•	0 I II	
WPBS 5		I 0 II	
WPBH 5		I 0 II	
WPBHP 5	•	I 0 II	
WPBS 6		I 0 II	
WPBH 6		I 0 II	
WPBHP 6	•	I 0 II	
WPBS 7		0 • I	
WPBH 7		0 • I	
WPBHP 7	•	0 • I	