



ENGLISH

Datasheet

RS Pro Pro Microwave Sensor fitting for High Bay

RS Stock No: 176-8524



This RS Pro LED Microwave Sensor fitting for High Bay and is compatible with the RS Pro range of High Bay's (176-8521 and 176-8565) With adjustable settings and a plug and play feature and 2m of power flex you can make this work best for any situation.





ENGLISH

Typical Properties

Detection zone Max.(D x H)

Detection sensitivity 100% / 75% / 50% / 25% / 10%

Hold time 5s / 30s / 90s / 3min / 20min / 30min

16 x 15m

Daylight sensor 50lux / 100lux / 200lux / Disabled

Mounting height 15m Max Motion detection 0.5~3m/s

Detection angle 150° (wall installation)

360°(ceiling installation)

Operating temperature -35 °C ~70 °C

Power consumption $\leq 0.6W(standby)$, <1W(operation)

Microwave Sensor Settings

Sensitivity	ON Time	Daylight Sensor	
1 2 3	4 5 6	7 8 9	
100% ● ● ●	5sec ● ● ●	Disabled ● ● ●	● ON
75% ○ ● ●	30sec ○ • •	200 Lux ○ • ○	^
50% ● ○ ●	90sec ● ○ ●	100 Lux ● O O	
25% ○ ○ ●	3min ○ ○ ●	50 Lux O O O	¥
10% 0 0 0	20min ● ● O		O OFF
	30min O O O		