

PRODUCT DATA SHEET

K4R Key-ring Floodlight (60lm) - POS12





2 - PRODUCT DATA SHEET V190719

K4R Key-ring Floodlight (60lm)

PRODUCT DESCRIPTION

High power in a small housing! The K4R is a key ring lamp raising performance, technology and design up to a new level. The small everyday helper in a high-quality and well-designed aluminium case reaches up to 60 lumens and provides wide area illumination. Being the first lamp in the K series, the K4R is rechargeable as well as equipped with an additional safety feature emitting an SOS (hold switch for 3 seconds) distress signal if necessary.

- Extremely compact in size yet very powerful with 60 lumens
- Rechargeable via supplied USB cable
- Wide area illumination of the surroundings
- Metal snap hook for easy attachment
- High-quality aluminium case

TECHNICAL DATA	
Length defocused [mm]	50
Head diameter [mm]	22
Weight incl. batteries [g]	17
Weight without batteries [g]	14
Focus function	No
Head material	ABS
Tube material	Aluminum alloy
Cartridge	No

POWER SUPPLY	
Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery description	Polymer 3.7V
Battery replaceable	Yes
Total battery voltage [V]	3.7
Total battery capacity [mAh]	180
Total battery energy ² [Wh]	0.67
Rechargeable	Yes
UN number	UN 3481
Energy modes	Energy Saving
Energy status indicator	Charge Indicator
	-

FURTHER SPECIFICATIONS		
IP class	IPXX	
Drop test (drop height) [m]	1	
Working temperature range [°C]	-20 to +40	

LIGHT FUNCTIONS

Power, S.O.S.

LIGHT SOURCE	
Amount LEDs	1
LED type	COB LED
Color temperature [K]	5500 to 6500
Color rendering index (CRI)	80

LIGHT VALUES	5		
ANSI – Energy Saving	Boost	Power	Mid Power Low Power
Light output ¹ [lm]		60	
Beam distance ¹ [m]		10	
Run time ¹ [h]		1.5	

SWITCH Front Switch



3 - PRODUCT DATA SHEET v190719



PACKAGING AND LOGISTICS

POS image TBC

PACKAGING INFORMATION			
Type of packaging	POS 12		
Supplied with	USB cable		
Item No.	502159		
Customs tariff number	85131000		
Color	black		
RRP ex / inc vat (£) - POS 12	£199.50/ £239.40		
RRP EURO ex / incl vat (€) - POS 12	€219.02 / €269.40		
SINGLE PACKAGE			
Dimensions W x H x D [cm]	TBC		
Gross weight [g]	TBC		
GTIN-13	TBC		

/ (EACH £16.62 / £19.95) / (EACH €18.25 / €22.45)

INNER CARTON	
Unit	TBC
Dimensions W x D x H [cm]	TBC
Gross weight [g]	TBC
GTIN-13	TBC

EXPORT CARTON	
Unit	TBC
Dimensions W x D x H [cm]	TBC
Gross weight [kg]	TBC
GTIN-13	TBC



4 - PRODUCT DATA SHEET V190719



PRODUCT SERIES

The Ledlenser K-Series The key to illumination.

The "K" in this series' name stands for "key". Because due to their compact sizes, people often keep these mini lights attached to their keychains in their pockets. But there's no reason to hide them - they have elegant designs, amazing power and are incredibly sturdy.

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

- 1) Measurements according to ANSI FL1 on the respective setting. Average values, in some cases, deviations by +/- 15 % may occur due to technical reasons. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting and to battery duration (hours/hrs/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If no setting is explicitly indicated, measurement is based on "energy saving mode."
- 2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.
- 5) Charging time varies by hardware used.

