



## **Datasheet**

## **RS Pro LED Panel Range**



<b>Product Code</b>	Model	Length	Width	Height
	600x600 Square Panel 4000K	595mm	595mm	34mm
	600x600 Square Panel 6000K	595mm	595mm	34mm
	1200x600 Panel 4000K	1200mm	595mm	34mm
	1200x600 Panel 6000K	1200mm	595mm	34mm
	Remote Emergency Pack 600x600	-	-	-
	Remote Emergency Pack 1200x600	-	-	-
	600x600 Surface Mounting Kit	1	-	1
	1200x600 Surface Mounting Kit	-	-	-

The RS Pro Backlit LED Panel range is a suitable solution for commercial applications. Available in both 4000 and 6000K offering both a cool/daylight lighting solution. This panel is fire rated to TPb standard and is compatible with a plug in 3hr emergency pack (sold separately). Available in both 600x600mm and 1200x600mm sizes, the RS Pro panel range offers flexibility to the installer. With its backlit LED configuration, throughout the life span of the product the light output remains uniform, without the risk of discolouration.

Product S Code	Supply Voltage	Power Factor	Wattage	Lumens	Luminaire Efficiency	Colour Temperature	Beam angle	CRI	IK Rating	Lifespan	Warranty
-	220-240V AC	≥0.9	36W	3600Lm	100 Lm/W	6000K	120°	≥80	IK02	30,000 Hrs	3 Years
-	220-240V AC	≥0.9	60W	6000Lm	100 Lm/W	4000K	120°	≥80	IK02	30,000 Hrs	3 Years
-	220-240V AC	≥0.9	60W	6000Lm	100 Lm/W	6000K	120°	≥80	IK02	30,000 Hrs	3 Years





