



Benefits

- Compact, bright and comfortable
- Long lifespan
- Up to 50% energy savings compared to CFL

Application



Model	Item Description	W	PF	lm	lm/W	CRI	BA	RoHS	Single Box Dimensions (LxWxH)mm	Outer Box Dimensions (LxWxH)mm	Packing Qty (PCS/CTN)
YTP38Z1-STKR-9W-E27	CLSV1 STKR 9W E27 3000K	9	0.5	900	100	>80	200°	20000	38*38*118	410*210*255	100
YTP38Z1-STKR-9W-E27	CLSV1 STKR 9W E27 4000K	9	0.5	900	100	>80	200°	20000	38*38*118	410*210*255	100
YTP38Z1-STKR-9W-E27	CLSV1 STKR 9W E27 6500K	9	0.5	900	100	>80	200°	20000	38*38*118	410*210*255	100

Application Conditions


IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C

Mechanical Properties


Optical Material	PC
Housing Material	PBT
Finishing Colour	White

Electrical Supply

Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC



Dimensional Drawing



YTP38Z1-STKR-9W-E27