
## CLASSIC





Dimension: mm NTS

## **TECHNICAL DATA**

Mode of Operation : Non-Maintained

Lamp : Maxspid 1W SMT LED Lamp

Rated Duration : 3 hrs and others
Mains Supply : 230 Volts, 50/60Hz

Power Consumption: < 1.6W

Battery : High temp Nickel Cadmium

Charge Monitor : Green LED Ø5mm
Test Facility : Push button switch

Safety Feature : Low volt cut-off preventing battery overdischarge

Housing : Injection moulded fire retardant high impact polycarbonate

diffuser and base. Clear reeded diffuser is designed for

non-glare and greater light distribution

Mounting : Wall or ceiling
Cable Entry : Ø20mm K/O hole
Weight : 1.0kg (gross)

Compliance : SS 563 : Part 1 & 2, SS IEC 60598-2-22

Warranty : 1 year

## **KEY FEATURES**

- > Using Surface Mount Technology LED
- > High Durability & Reliability
- > Low Heat
- > Low Maintenance
- > Low Power Consumption
- > No "Black Ends"

ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Model	Lamp	Battery type
JW/NM/W5100	1W SMT LED	Nickel Cadmium

Note:

Optional silkscreen printed legend on cover to convert into an emergency exit light. \*Heating strip applicable (for cold room used)

Heating strip applicable (for cold room us









