

HTT 150-211

SUPRATEC HTC | Ultraviolet lamps



Areas of application

- Curing large areas of plastic
- Drying paint and varnishes
- Glue curing
- Exposure of diazo film material and print masters
- Artificial material aging
- Fluorescence excitation (with black glass filters)
- Curing large areas of plastic

Product features

- SUPRATEC UV high pressure lamps for technical applications





Product datasheet

Technical data


Electrical data

Nominal wattage	150.00 W
Nominal voltage	230 V
Nominal current	1.5 A
Construction voltage	230 V
Lamp voltage	230 V

Photometrical data

Radiated power 315400 nm (UVA)	22 W
Radiated power 280315 nm (UVB)	6 W

Dimensions & weight



Diameter	10.0 mm
Length	57.6 mm
Light center length (LCL)	10.0 mm

Lifespan

Lifespan	1000 h ¹⁾
·	

¹⁾ Economic lifespan

Additional product data

Capabilities

Burning position	p20/s70

Country specific information

Product datasheet

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321912848	OSRHTT150-211	-	-	-

Product datasheet

Attention

SUPRATEC lamps emit UV radiation of high intensity which can cause sunburn and conjunctivitis. Skin or eyes must not be exposed to direct or reflected unfiltered radiation! Operate in closed fixtures only.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321912848	HTT 150-211	Folding carton box 1	33 mm x 33 mm x 113 mm	0.12 dm ³	26.00 g
4008321912855	HTT 150-211	Shipping carton box 25	130 mm x 180 mm x 180 mm	4.21 dm ³	625.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.